

Lighting Your Life Since 1970

Product Specifications - 12165WCAT			
Job Name:	Job Type:		
Quantity:	Comments		



12165WCAT

Castello 3-Light Invert Bowl Pendant

N/A

N/A

N/A

FinishGlass/ShadeProduct CategoryArtesian BronzeWax CandleInvert Bowl Pendant

Measurements

1 2	m	n	in	^
La	,,,	μ	ш	У

Lamping	
Number of Bulbs	3
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	300
Rated Life	±2,500 Hours
Rated Lumens	±3,450
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Width	25.0"
Height	34.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	19.6 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"

	Shipping	
"	Carton Weight	19.6 lbs
"	Carton Width	24"
1	Carton Height	32"
١	Carton Length	25"
١	Carton Cubic Feet	11.14
١	Master Pack	1
١	Master Pack Weight	N/A
١	Master Pack Width	N/A
١	Master Pack Height	N/A
3	Master Pack Length	N/A
١	Master Cubic Feet	N/A
١	UPS Shippable	Oversize

Cofety Deting	Dry LIDC Code	702200020000 Incondescen
Certification	Other	Equivalents

Canopy Width

Canopy Height

Canopy Length

				_ 9 000
Safety Rating	Dry	UPC Code	783209029880	Incand
Energy Star	No	Shades Included	N/A	Fluore
CA Title 24	No	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	No	Conversion Kit	N/A	
Dark Sky	N/A	Material	Steel	

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.