

Lighting Your Life Since 1970

	Product Specifications - 85010LTES			
I	Job Name:	Job Type:		
l				
ſ	Quantity:	Comments		
l				



85010LTES

Odessa EE 1-Light Outdoor Pole/Post Lantern

Finish	Glass/Shade	Product Category
Espresso	Latte	Outdoor Pole/Post Mount

No

Lamping	
Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	18
Max Fixture Wattage	18
Rated Life	±10,000 Hours
Rated Lumens	±1,355
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	81-82
Photo Cell Included	N/A
Ballast/Driver/Transformer	No

Dimmable

Measurements	
Width	9.0"
Height	20.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	2.7 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

	Shipping	
"	Carton Weight	2.7 lbs
"	Carton Width	11'
١	Carton Height	28'
١	Carton Length	12'
١	Carton Cubic Feet	2.10
٨	Master Pack	1
١	Master Pack Weight	N/A
١	Master Pack Width	N/A
١	Master Pack Height	N/A
3	Master Pack Length	N/A
١	Master Cubic Feet	N/A
١	UPS Shippable	Yes

Certification		Other		Equivalents	
Safety Rating	Wet	UPC Code	783209023055	Incandescent Watts	123
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	Yes	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Die Cast Aluminum		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.