

# Lighting Your Life Since 1970

Product Specifications - 85054HOVR			
Job Name:	Job Type:		
Quantity:	Comments		



# 85054HOVR

Coldwater EE 1-Light Outdoor Wall Lantern

Finish	Glass/Shade	Product Category
Acid Verde	Honey	Outdoor Wall Mount

I am	nII	$^{n}$
Laiii	γII	19
	٠.	_

Lamping	
Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	26
Max Fixture Wattage	26
Rated Life	±10,000 Hours
Rated Lumens	±1,760
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	Yes
Ballast/Driver/Transformer	No
Dimmable	N/A

Measurements	
Width	9.0"
Height	16.0"
Length	N/A
Extension	10"
Back Plate Width	N/A
Back Plate Height	N/A
НСО	6"
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	6.6 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A

N/A

Shipping	
Carton Weight	6.6 lbs
Carton Width	11"
Carton Height	18"
Carton Length	14"
Carton Cubic Feet	1.53
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

N/A N/A

### Certification Other **Equivalents**

**Canopy Length** 

00.1041.0		0 (1101		=quivaronto
UL Standard	Wet	UPC Code	783209023208	Incandescent Watts
Energy Star	No	Shades Included	N/A	Fluorescent Watts
CA Title 24	No	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	No	Conversion Kit	N/A	
Dark Sky	N/A	Material	Aluminum	

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.