

Lighting Your Life Since 1970

Product Specifications - 86926BK	
Job Name:	Job Type:
Quantity:	Comments



86926BK

1-Light Outdoor Wall Mount



5.50"

10.00"

4.50"

4.50"

2 50"

N/A

6"

Finish Black

Lamping

Number of Bulbs **Light Type**

Bulb Type Max Bulb Wattage **Max Fixture Wattage Rated Life** ±10,000 Hours **Rated Lumens Color Temp** ±2,700 K Bulb(s) Included Light Up/Down

Photo Cell Included Ballast/Driver/Transformer **Dimmable**

Glass/Shade

Frosted

Width

Measurements

Fluorescent Height GU24 Length 13 Extension 13 ±900 N/A N/A 81-82

N/A

No

No

Yes

Yes

No

No

N/A

Back Plate Width Back Plate Height HCO Min Overall Height Max Overall Height **Hanging Weight** 2.50 lbs **Height Adjustable** Slope **Chain Length** Wire Length **Canopy Width Canopy Height**

Product Category Outdoor Wall Mount

Shipping

Carton Weight 2.50 lbs **Carton Width** 6" **Carton Height** 11" **Carton Length** 7" **Carton Cubic Feet** 0.30 **Master Pack** 6 **Master Pack Weight** 16.74 lbs Master Pack Width 19.90" Master Pack Height 12 40" **Master Pack Length** 15.00" **Master Cubic Feet** 2 14 **UPS Shippable** Yes

Certification Safety Rating

Energy Star

CA Title 24

CA Title 20

Dark Sky

ADA

Beam Spread

Canopy Length

Other Wet UPC Code 783209099890 Shades Included N/A **Crystals Included** N/A Diffuser Included N/A **Conversion Kit** N/A Material Die Cast Aluminum

Equivalents

Incandescent Watts 82 **Fluorescent Watts** N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.