

Lighting Your Life Since 1970

	Product Specifications - 89932WT					
I	Job Name:	Job Type:				
l						
ſ	Quantity:	Comments				
l						



Certification

Safety Rating

Energy Star

CA Title 24

CA Title 20

Dark Sky

ADA

89932WT

CounterMax MX-L120DL 7" 2700K LED Under Cabinet

Equivalents

Fluorescent Watts

N/A

N/A

783209104259 Incandescent Watts

N/A

N/A

N/A

N/A N/A

Finish		Glass/Shade		Product Category	
White		Clear		Under Cabinet	
Lamping		Measurements		Shipping	
Number of Bulbs		Width	4.00"	Carton Weight	1.32 lbs
Light Type	LED	Height	1.00"	Carton Width	6"
Bulb Type		Length	7.00"	Carton Height	3"
Max Bulb Wattage	5.1	Extension	N/A		9"
Max Fixture Wattage	5.1	Back Plate Width	N/A	Carton Cubic Feet	0.08
Rated Life	±50,000 Hours	Back Plate Height	N/A	Master Pack	6
Rated Lumens	±289	HCO	N/A	Master Pack Weight	12.12 lbs
Color Temp	±2,700 K	Min Overall Height	N/A	Master Pack Width	9.84"
Bulb(s)	Not Included	Max Overall Height	N/A	Master Pack Height	9.45"
Light Up/Down	N/A	Hanging Weight	1.32 lbs	Master Pack Length	12.40"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	0.67
CRI	82	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	Standard/Lutron® or Leviton® LED	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Other

Dry UPC Code

N/A

No Shades Included

No Crystals Included

No Diffuser Included

No Conversion Kit

Material

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.