

Lighting Your Life Since 1970

	Product Specifications - 89934WT					
ſ	Job Name:	Job Type:				
L						
ſ	Quantity:	Comments				
l						



90024WT

CounterMax MX-L120DL 21" 2700K LED Under Cabinet

Finish		Glass/Shade		Product Category	
White		Clear		Under Cabinet	
Lamping		Measurements		Shipping	
Number of Bulbs		Width	4 00"	Carton Weight	2.76 lbs
Light Type	LED	Height	1.00"	Carton Width	6"
Bulb Type	LLD	Length	21.00"	Carton Height	3"
Max Bulb Wattage	10	Extension	N/A	Carton Length	23"
Max Fixture Wattage	10	Back Plate Width	N/A	Carton Cubic Feet	0.20
Rated Life	±50,000 Hours	Back Plate Height	N/A	Master Pack	6.20
Rated Lumens	±587	HCO	N/A	Master Pack Weight	20.72 lbs
Color Temp	±2,700 K	Min Overall Height	N/A	Master Pack Width	12.44"
Bulb(s)	Not Included	Max Overall Height	N/A	Master Pack Height	9.45"
Light Up/Down	N/A	Hanging Weight	2.76 lbs	Master Pack Length	23.81"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	1.62
CRI	82	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A	• •	
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	Standard/Lutron® or Leviton® LED	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		
		-			

Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209104310	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	N/A		

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.