

Lighting Your Life Since 1970

Product Specifications - 87462AL			
Job Name:	Job Type:		
Quantity:	Comments		



87462AL

CounterMax MX-X12-LX 3-Light Xenon Starter Kit

Finish	Glass/Shade	Product Category
Brushed Aluminum		Under Cabinet Kit

Lamping	
Number of Bulbs	3
Light Type	Xenon
Bulb Type	12V Wedge T5 Xelogen
Max Bulb Wattage	18
Max Fixture Wattage	54
Rated Life	±10,000 Hours
Rated Lumens	±729
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Low-Voltage

Measurements	
Width	5.0"
Height	1.0"
Length	21.0"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	2.3 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

	Shipping	
"	Carton Weight	2.3 lbs
"	Carton Width	8"
"	Carton Height	4"
4	Carton Length	24"
4	Carton Cubic Feet	0.40
4	Master Pack	5
4	Master Pack Weight	18.3 lbs
4	Master Pack Width	8.5"
4	Master Pack Height	21.5"
s	Master Pack Length	24.8"
4	Master Cubic Feet	2.62
4	UPS Shippable	Yes
4		

Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209074743	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Aluminum		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.