

G 7156 SCVi SF

Fully integrated dishwashers
with 3D MultiFlex Tray for maximum convenience.



- QuickIntenseWash, superior cleaning and drying in under 60 min
- Everything completely dry – AutoOpen drying
- Very easy door opening and closing – ComfortClose
- Clean Touch Steel front with handle in ContourLine design

EAN: 4002516569145 / Material number: 12055090 / Old Material Number: 21715665USA

Construction type	
Fully integrated dishwashers	•
24 inch dishwasher	•
Design	
Fascia color	Stainless Steel.
Fascia panel version	Fully integrated fascia
Control type	Programme selector button
Control panel	1-line text display
Display color	White
MultiLingua	•
Convenience	
Door closing aid	ComfortClose
Operating noise dB(A) re 1 pW	43
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indication	Display
Display language selection	•
Efficiency and sustainability	
EcoFeedback	•
EcoPower Technology	•
Proven hygiene	•
Hot water connection	•
Half load	•
ENERGY STAR® Most Efficient	•
Gentle on dishware/glass	
Fresh water dishwasher	•
AutoOpen drying	•
SensorDry	•
Active condensation drying	•
Perfect GlassCare	•
Dishwashing programs	
QuickIntenseWash	•
Normal	•
Pots & Pans	•
IntenseWash	•
China & Crystal	•
SaniWash	•
Rinse & Hold	•
Rinse options	
IntenseZone	•
Express	•
Extra Clean	•
Extra dry	•
Basket design	
Cutlery loading	3D MultiFlex tray
FlexCare glass holder	2
FlexCare cup rack	2
Basket design	ExtraComfort 60 cm
Safety	
Waterproof system	•

G 7156 SCVi SF

Fully integrated dishwashers
with 3D MultiFlex Tray for maximum convenience.



EAN: 4002516569145 / Material number: 12055090 / Old Material Number: 21715665USA

Check filter saturation indicator

•

Child Safety lock

•

Technical data

Niche width min in in.(mm) 23 5/8 (600)

Niche width max in in.(mm) 23 5/8 (600)

Niche height min in in.(mm) 33 3/4 (855)

Niche height max in in.(mm) 36 1/4 (920)

Niche depth in in.(mm) 22 1/2 (570)

Appliance width in in.(mm) 23 5/8 (598)

Appliance height in in.(mm) 33 3/4 (855)

Appliance depth in in.(mm) 21 3/4 (550)

Appliance depth with door open in in.(cm) 47 1/2 (120.5)

Net weight in lbs. (kg) 117 (53.0)

Total connected load in kW 1.40

Voltage in V 120

Fuse rating in A 15

Number of phases 1

Electrical frequency standard 60

Length of water inlet hose in ft (m) 5 (1.50)

Length of water drain hose in ft (m) 5 (1.50)

Length of electrical wire in ft (m) 4 (1.20)

Available display languages

Available display languages via MultiLingua

deutsch, english, español,
français, português,