

G 5056 SCVi

Fully integrated dishwashers

in tried-and-tested Miele quality at an affordable entry-level price.



- QuickIntenseWash, superior cleaning and drying in under 60 min
- Save up to 50% more electricity – hot water connection
- Comfort Baskets w/Original Tray adjusts for easy loading
- Very easy door opening and closing – ComfortClose
- Maximum versatility – Height-adjustable upper basket

EAN: 4002516376132 / Material number: 11636720 / Old Material Number: 21505662USA

Construction type	
Fully integrated dishwashers	•
24 inch dishwasher	•
Design	
Fascia color	Stainless Steel.
Fascia panel version	Fully integrated fascia
Control type	Programme selector button
Control panel	3-digit 7-segment display
Display color	Yellow
Convenience	
Door closing aid	ComfortClose
Operating noise dB(A) re 1 pW	44
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indication	acoustic
Efficiency and sustainability	
EcoPower Technology	•
Proven hygiene	•
Hot water connection	•
ENERGY STAR® Most Efficient	•
Gentle on dishware/glass	
Fresh water dishwasher	•
Active condensation drying	•
Dishwashing programs	
QuickIntenseWash	•
Normal	•
Pots & Pans	•
SaniWash	•
Rinse & Hold	•
Rinse options	
Short	•
Extra Clean	•
Extra dry	•
Basket design	
Cutlery loading	Cutlery tray
FlexCare cup rack	1
Basket design	Comfort
Safety	
Waterproof system	•
Technical data	
Niche width min in in.(mm)	23 5/8 (600)
Niche width max in in.(mm)	23 5/8 (600)
Niche height min in in.(mm)	33 3/4 (855)
Niche height max in in.(mm)	36 1/4 (920)
Niche depth in in.(mm)	21 3/4 (550)
Appliance width in in.(mm)	23 5/8 (598)
Appliance height in in.(mm)	33 3/4 (855)
Appliance depth in in.(mm)	22 1/2 (570)
Appliance depth with door open in in.(cm)	47 1/2 (120.5)
Net weight in lbs. (kg)	100 (45.0)

G 5056 SCVi

Fully integrated dishwashers

in tried-and-tested Miele quality at an affordable entry-level price.



EAN: 4002516376132 / Material number: 11636720 / Old Material Number: 21505662USA

Total connected load in kW	1.40
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in ft (m)	5 (1.50)
Length of water drain hose in ft (m)	5 (1.50)
Length of electrical wire in ft (m)	4 (1.20)
Min. front panel weight in kg	4.0
Max. front panel weight in kg	11.0
[can be retrofitted by Service to min.]	7.0
[can be retrofitted by Service to max.]	14.0