

# INSTALLATION INSTRUCTIONS For Fixture #3288-589

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**  
**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

## PREPARING THE FIXTURE (FIG. 1)

1. Shut off the power supply at the fuse box or circuit breaker. If necessary, remove the old fixture from ceiling, including the mounting hardware.
2. Carefully remove the fixture from the carton and check that all parts are included as show in Figure 1.

## MOUNTING THE FIXTURE (FIG. 2)

3. Attached the Cross bar (A) to the outlet box using the 2 Outlet Box Screws (C). The side of the Cross bar (A) marked "GND" must face out.
4. While holding the steel pan (D) towards the Crossbar (A), connect the electrical wires as shown in figure 2. If your outlet has a ground wire (green or bare copper), connect the fixture Ground Wire to it. Otherwise, connect the fixture ground wire directly to the crossbar using the green screw provided. Make sure that all wire connectors are secured. Tuck the wire connections neatly into the ceiling junction box as you are holding the fixture assembly toward the ceiling.
5. Finishing mounting the fixture pan (I) by placing it over both mounting screws (B) so that the screws protrude through the key holes in the steel pan (D). Rotate the pan (D) until the screws are seated in the slots of the key holes and tighten the screws with a screwdriver.
6. Thread the Nipple (F) into the Coupling (E), and secure with hex nut.
7. Install the light bulbs in accordance with the fixture's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**
8. Put the glass shade (G), rubber washer (H), steel washer (I) over the nipple (F) in order, then secure with hex nut (J).
9. Put the cap (K) over the nipple (F) and secure with finial (L)

Your installation is now complete.  
 Return power to the junction box to test the fixture.

