

# INSTALLATION INSTRUCTIONS

For Model # 5993-84/5994-84/5995-84(New 01/03/2003)

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**

## MOUNTING THE FIXTURE (Fig. 1)

1. Shut off power at the circuit breaker and remove old fixture from wall, including the crossbar.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Secure Circular Strap (A) using Screw (C) to the Outlet Box. The side of the Circular Strap marked "GND" must face out.

## CONNECTING THE WIRES (Fig. 2)

4. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's Ground Wire to it. Otherwise, connect the fixture's Ground Wire directly to the Circular Strap by using the Green Screw provided.

## FINISHING THE INSTALLATION (Fig. 1)

5. Place Fixture Body (D) over the Circular Strap (A) then secures them tightly with two Screw Stud (B).
6. Install halogen bulb into socket in accordance with the fixture's specifications. (**DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**)
7. Insert Bulb Shield (H) onto the socket, then using the screw (I) secure them carefully by screwdriver. The two screw on both side must screw into the groove on the glass shield (H)
8. Place glass shade (E) over the socket, then secure it by screw the metal ring (F) into the socket cup. Tighten the metal ring (F) with provide wrench (J).

Your installation is now complete. Return power to the outlet box and test the fixture.

MIN 90°C SUPPLY CONDUCTORS

