

INSTALLATION INSTRUCTIONS

For Models 977-1 U.S.Patent No: D588,304

This product is protected by United States Federal and/or State Law, including Patent and/or Copyright laws.

© Minka Lighting Inc.

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE

1. Shut off power at the fuse box or circuit breaker box. Remove the old fixture from ceiling, including the crossbar.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to loose any small parts necessary for installation.
3. Thread the two Mounting Screws (A) on crossbar about 1/4", align with the pre-drilled holes in the canopy (D).
4. Attach the crossbar (B) to the outlet box using the two screws (C) from the outlet box. The side of the crossbar marked "GND" and with two mounting screws must face out.
5. Feed wire through rods (F) as required getting desired height. While holding the center tube (F) turn counter-clockwise four full turns. Attach each additional center tube (F) by turning it clockwise until assembled.
6. While holding the canopy (D) toward the ceiling, connect the electrical wires as follows (See Figure 2). Connect the black wire from the fixture to the black house (hot) wire. Connect the white wire from the fixture wire to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet has a ground wire (green or bare copper), connect fixture's ground wire to it. Otherwise connect fixture's ground wire directly to the crossbar using the green screw provided. Tuck the wire connections neatly into the ceiling junction box as you hold the canopy (D) assembly toward the ceiling.
7. Attach the canopy (D) onto outlet box and secure it with nuts (E).
8. Place the metal frame (H) and glass shade (J) over the socket (G). Then secure the glass with retaining ring (I).
9. Install the light bulbs in accordance with fixtures specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

Fig.1





Fig. 2



LA-1849E



american lighting association