

MISENO

— TAKE ME HOME —

BronzeStep Underlayment

Model MFLR-FU81326



This 2-in-1 underlayment is suitable for all standard laminate and engineered floating floors. BronzeStep is designed for use on wood and concrete subfloors. This underlayment is designed to smooth out minor subfloor imperfections while providing excellent moisture resistance through the laminated moisture barrier attached to BOTH sides of the foam. Special moisture resistant flap with self-sealing tape supports easy installation.

Features

- Humidity, mold and mildew resistant
- Double-faced moisture barrier

Installation

- 1) Roll BronzeStep underlayment over the sub-floor with the tape side facing up for easy installation.
- 2) End seams need to be butted together flush, do not overlap the pad. Tape the end seams.
- 3) Install flooring according to the manufacturer's installation instructions.

Approved Substrates

- Dry, cured concrete
- Concrete and masonry blocks
- Cement backer units (CBU) and cement terrazzo floors
- Wood, plywood, or OSB sub-floors that meet applicable building codes.

Limitations

BronzeStep is not suitable for use as underlayment for Ceramic Tile, Glued-down wood, Sheet vinyl, and VCT.

Installations over concrete in high moisture areas (Vapor emission rate above 3 lbs/ 1000 sq ft/ 24 hrs) will require additional protection such as Miseno Moisture Barrier.

Specifications

Physical Properties

Dimensions.....100 sf (30'x40"x2mm)

Thickness.....0.079"

Underlayment comparison chart

	Smooths Sub-floor	Moisture Barrier	Approved For Radiant Heat	IIC*	STC*	Thickness	Side-wicking*	Material
SuperFoam 100 sf roll	●	●	●	71	59	3.2mm	●	Foam
GoldStep 100 sf roll	●	●	●	71	66 & 54	3.2mm	●	Fiber
SilverStep 100 sf folded	●	●	●	72	66	3.2mm		XLPE*
BronzeStep 100 sf roll	●	●				2mm		Foam

*Industry Terms

Ambient Sound:

This is the sound that travels within a room. Underlayments can affect the quality and volume of ambient sounds within a room. When it comes to walking on a floor, a good underlayment can make a floating floor sound more like a solid wood floor.

IIC

(Impact Insulation Class):

This is the measurement of impact sound that passes through the floor to a room below; for example walking in high heeled shoes, running, bouncing a ball, dropping objects.

STC (Sound

Transmission Class):

This is the measurement of airborne sound that passes through the floor to a room below; for example talking, radios, vacuums.

XLPE

(High Density, Cross-Linked Polyethylene):

A dense foam similar to camping mats, but thinner. A highly moisture resistant vapor barrier with excellent cushioning qualities.

Open & Closed

Cell Polyethylene:

This is the basic foam that most underlayments are made of. Often sold with an added laminated moisture barrier.

Moisture Barriers:

Many underlayments are advertised as "3-in-1" products. These cushion, cut sound and have added moisture barriers. With these an additional layer of PE (Polyethylene) film is laminated making them even more able to resist high moisture levels. Some underlayments cannot function without an added moisture barrier (cork, fiber and some thinner open & closed cell foams). In these cases an additional minimum 6-mil (6/1000 inch) must be laid between the sub-floor and the padding. All MISENO branded underlayments have laminated moisture barriers and flaps.

Side-wicking

(Moisture Side-wicking)

When installed properly, Goldstep and Superfoam can wick sub-floor or incidental perimeter moisture and disperse it through the pad. Moderate amounts of moisture will eventually dissipate over time by perimeter or sub-floor evaporation, provided the source of water such as a leak is stopped.

"Flaps" and Seaming:

When rolls of underlayment are laid side-to-side, that seam becomes an entry point for moisture and therefore must be taped. Since taping butt-seams can lead to leakage, most quality underlayments have plastic flaps which overlay the prior row. These are then taped with duct or packing tape, as are end seams and tears or holes in the padding.