



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,059
Weight Density:	103,003
Stitches Per Inch:	11.5 (45.28 per 10 cm)
Finished Pile Thickness:	.101" (2.57 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® Nylon
Face Weight:	17.0 oz. per sq. yd. (576 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, VerticalAshlar, BrickAshlar, QuarterTurn, MultiDirectional
Soil Release Technology:	Sentry Plus
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	44%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Static, Lifetime Limited Tile Warranty
-------------	---



7131
Madras




7878
Mudslide



7968
Smoky Martini



7585
Sea Breeze



7989
Black Velvet