



ECUPP EQ290

Specification

Product Type:	Carpet Tile
Construction:	Tufted
Surface Appearance:	Textured Patterned Loop
Gauge:	1/12" (47.00 rows per 10 cm)
Pile Weight:	17 oz/yd ² (576 g/m ²)
Pile Thickness:	.095" (2.41 mm)
Stitches Per Inch:	11.0 (43.34 per 10 cm)
Dye Method:	Solution Dyed / Yarn Dyed
Fiber Type:	Colorstrand® Nylon
Stain Release Technology:	Sentry Plus Stain Protection
Soil Release Technology:	Sentry Soil Protection
Density:	6,442
Weight Density:	109,515
Backing Materials:	EcoFlex ICT
Installation Method:	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn / Multi Directional
Size:	24" x 24" (.6096 m x .6096 m)
Flammability:	ASTM E 648 Class I (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
IAQ Green Label Plus:	1098
NSF 140:	Gold
CRI Appearance Retention Rating:	Severe Traffic
Warranties:	Lifetime Limited Carpet Tile Warranty Lifetime Static

All specifications are subject to normal manufacturing tolerances.

6/18



MANUFACTURING / EXTRACTION LOCATIONS

Manufacturing Location: Glasgow, VA 24555

PRODUCT ATTRIBUTES

Pre-Consumer Recycled Content: 48%

Post-Consumer Recycled Content: 0%

Closed Loop / Take Back Program: ReCover Program

Recyclable: 100%

TVOC Range: 0.5 mg/m³ or less

CERTIFICATIONS/LABELS/DECLARATIONS

CDPH v1.1-2010 Compliant: Yes

Living Building Challenge (LBC) Declaration: LBC Declared

Indoor Air Quality: [GLP1098](#)

NSF 140 Certification: [EcoFlex ICT Gold](#)

Declare Label: [EcoFlex ICT](#)

Environmental Product Declaration: [EcoFlex ICT](#)