



Product Name & Number:	Forest Oaks 3" WEC36 32288
Collection:	Lineage
Construction:	Engineered
Face Species:	Quercus, spp USA
Core Species:	Poplar
Number of Plies:	5
Thickness:	3/8"
Width:	3"
Grade:	Standard
Profile:	Kissed Edges/Kissed Ends
Face Finish:	Flat
Finish Treatment:	Aluminum Oxide with ScotchGard Repel
Gloss Level:	38° + or - 5°
Sq. Ft. per Carton:	28.25
Sq. Ft. per Pallet:	1130
Cartons per Pallet:	40
Weight per Carton:	32 lbs
Weight per Pallet:	1280 lbs
Installation:	Glue Down/Nail/Staple/Float
	On/Above Grade
	Wood/Concrete
Warranties:	25 year Finish
	Lifetime Structure
	Lifetime Moisture
Janka Hardness:	1290
Photo Sensitivity:	1
Character Variation:	Medium
Sound Transmission (STC):	
MoistureGuard:	53
SilentGuard:	54
Impact Insulation Class (IIC):	
MoistureGuard:	60
SilentGuard:	61

Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

PRODUCT SPEC SHEET



3-11-11 Update

Color Name	Color Number	Quarter Round		Reducer		T-Molding		Baby Threshold		Stairnosing		Wood Filler
Natural	10	HQRTA	05012	HREDC	05012	HTMDA	05012	HENDD	05012	HFSTC	05012	WF627
Golden	20	HQRTA	05011	HREDC	05011	HTMDA	05011	HENDD	05011	HFSTC	05011	WF639
Autumn	30	HQRTA	05239	HREDC	05239	HTMDA	05239	HENDD	05239	HFSTC	05239	WF676
Cherry	42	HQRTA	05088	HREDC	05088	HTMDA	05088	HENDD	05088	HFSTC	05088	WF-638
Oxford	52	HQRTA	05183	HREDC	05183	HTMDA	05183	HENDD	05183	HFSTC	05183	WF-651

Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch.

PRODUCT SPEC SHEET