



Product Name & Number:	Marbury Oak – WEL13
Collection:	Lineage
Construction:	Engineered
Face Species:	White Oak (Quercus, spp USA)
Core Species:	Poplar
Number of Plies:	Multi
Thickness:	3/8"
Width:	3"
Grade:	Standard
Profile:	Kissed Edges/Square Ends
Face Finish:	Smooth
Finish Treatment:	Aluminum Oxide with Scotchgard Repel
Gloss Level:	38° + or - 5°
Sq. Ft. per Carton:	24
Sq. Ft. per Pallet:	960
Cartons per Pallet:	40
Weight per Carton:	36.2 lbs
Weight per Pallet:	1448.2 lbs
Installation:	Glue Down/Nail/Staple/Float On/Above Grade
Warranties:	15 year Finish Lifetime Structure Lifetime Moisture
Smoke Density:	Under 450
Janka Hardness:	1290
Photo Sensitivity:	1
Character Variation:	Medium
Critical Radiant Flux:	
Direct Glue:	Class 2
Mechanically Attached:	Class 2
Floating:	
Static Coefficient of Friction:	
Dry:	.72
Wet:	.53
Sound Transmission (STC):	
MoistureGuard:	53
SilentGuard:	54
Impact Insulation Class (IIC):	
MoistureGuard:	60
SilentGuard:	61

PRODUCT SPEC SHEET



3-11-11 Update

Color Name	Color Number	Quarter Round		Reducer		T -Molding		Baby Threshold		Stairnoise		Wood Filler	
Natural	10	HQRTA	05012	HREDC	05012	HTMDA	05012	HENDD	05012	HFSTC	05012	WF	627
Honey	20	HQRTA	05072	HREDC	05072	HTMDA	05072	HENDD	05072	HFSTC	05072	WF	639
Latte	30	HQRTA	05178	HREDC	05178	HTMDA	05178	HENDD	05178	HFSTC	05178	WF	676
Saddle	40	HQRTA	05184	HREDC	05184	HTMDA	05184	HENDD	05184	HFSTC	05184	WF	651
Russet	50	HQRTA	05086	HREDC	05086	HTMDA	05086	HENDD	05086	HFSTC	05086	WF	693

Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch.

PRODUCT SPEC SHEET