



Product Name & Number:	Warrenton 3" WEC38 - 32305
Collection:	Revival
Construction:	Engineered
Face Species:	Carya
Core Species:	Poplar
Number of Plies:	5
Thickness:	3/8"
Width:	3"
Grade:	Standard
Profile:	Kissed Edges/Kissed Ends
Face Finish:	Flat
Finish Treatment:	Aluminum Oxide with ScotchGard Repel
Gloss Level:	38° + or - 5°
Sq. Ft. per Carton:	28.25
Sq. Ft. per Pallet:	1130
Cartons per Pallet:	40
Weight per Carton:	41 lbs
Weight per Pallet:	1640 lbs
Installation:	Glue Down/Nail/Staple/Float
	On/Above Grade
	Wood/Concrete
Warranties:	25 year Finish
	Lifetime Structure
	Lifetime Moisture
Janka Hardness:	1820
Photo Sensitivity:	3
Character Variation:	Medium
Sound Transmission (STC):	
MoistureGuard:	53
SilentGuard:	54
Impact Insulation Class (IIC):	
MoistureGuard:	60
SilentGuard:	61

Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

PRODUCT SPEC SHEET



Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch.

Color Name	Color Number	Stair Noising		Reducer		Baby Threshold		T-Molding		Quarter Round		Wood Filler	
		HFSTC		HREDC		HENDD		HTMDA		HQRTA		WF	
Natural	10	HFSTC	05145	HREDC	05145	HENDD	05145	HTMDA	05145	HQRTA	05145	WF	693
Warm Cherry	16	HFSTC	05002	HREDC	05002	HENDD	05002	HTMDA	05002	HQRTA	05002	WF	646
Golden Carmel	20	HFSTC	05126	HREDC	05126	HENDD	05126	HTMDA	05126	HQRTA	05126	WF	635
Suede	82	HFSTC	05237	HREDC	05237	HENDD	05237	HTMDA	05237	HQRTA	05237	WF	677
Thrasher Brown	92	HFSTC	05060	HREDC	05060	HENDD	05060	HTMDA	05060	HQRTA	05060	WF	637

PRODUCT SPEC SHEET