



<b>Product Name &amp; Number:</b>	<b>Zanzibar – WEK3 - 32082</b>
<b>Collection:</b>	<b>Artiquity</b>
<b>Construction:</b>	<b>Engineered</b>
<b>Face Species:</b>	<b>Varies by color</b>
<b>Core Species:</b>	<b>Poplar</b>
<b>Number of Plies:</b>	<b>9</b>
<b>Thickness:</b>	<b>1/2"</b>
<b>Width:</b>	<b>5"</b>
<b>Grade:</b>	<b>Standard</b>
<b>Profile:</b>	<b>Hand beveled Edges/Hand beveled Ends</b>
<b>Face Finish:</b>	<b>Handscrapped</b>
<b>Finish Treatment:</b>	<b>Matte Aluminum Oxide</b>
<b>Gloss Level:</b>	<b>25° + or - 5°</b>
<b>Sq. Ft. per Carton:</b>	<b>19.69</b>
<b>Sq. Ft. per Pallet:</b>	<b>1023.88</b>
<b>Cartons per Pallet:</b>	<b>52</b>
<b>Weight per Carton:</b>	<b>Varies by color</b>
<b>Weight per Pallet:</b>	<b>Varies by color</b>
<b>Installation:</b>	<b>Direct Glue/Nail/Staple/Float On/Above/Below Grade Wood/Concrete Subfloor</b>
<b>Warranties:</b>	<b>25 year Finish Residential Lifetime Structure Residential Lifetime Moisture Residential 5 year Light Commerical</b>
<b>Certifications</b>	<b>Floor Score Forest Stewardship Council FSC Number SCS-COC-003140 Carb Phase 2 compliant</b>
<b>Critical Radiant Flux:</b>	
<b>Direct Glue:</b>	<b>Class 1</b>

## **PRODUCT SPEC SHEET**



**Mechanically Attached**                      **Class 1**  
**Smoke Density:**                              **Under 450**  
**Janka Hardness:**                              **See Chart**  
**Photo Sensitivity:**                           **See Chart**  
**Character Variation:**                        **See Chart**  
**Sound Transmission (STC):**  
    **MoistureGuard:**                         **54**  
    **SilentGuard:**                              **54**  
**Impact Insulation Class (IIC):**  
    **MoistureGuard:**                         **59**  
    **SilentGuard:**                              **59**

7-29-11 Update

Color Name	#	Quarter Round		Reducer		T-Molding		Baby Threshold		Stairnosing		Wood Filler	Janka	Photo	Character
Burmese Teak Natural	01	HQRTA	05035	HREDD	05035	HTMDA	05035	HENDD	05035	HFSTD	05035	WF637	1000	4	Med/Low
Santos Mahogany Natural	02	HQRTA	05074	HREDD	05074	HTMDA	05074	HENDD	05074	HFSTD	05074	WF651	2200	4	Med/Low
<b>African Hickory Natural</b>	<b>03</b>	<b>HQRTA</b>	<b>05055</b>	<b>HREDD</b>	<b>05055</b>	<b>HTMDA</b>	<b>05055</b>	<b>HENDD</b>	<b>05055</b>	<b>HFSTD</b>	<b>05055</b>	<b>WF651</b>	<b>1574</b>	<b>3</b>	<b>Low</b>
Antique Heart Pine	04	HQRTA	05045	HREDD	05045	HTMDA	05045	HENDD	05045	HFSTD	05045	WF676	690	5	Medium
Antique Elm Walnut	05	HQRTA	05213	HREDD	05213	HTMDA	05213	HENDD	05213	HFSTD	05213	WF651	860	2	Low
Antique Elm Chestnut	06	HQRTA	05027	HREDD	05027	HTMDA	05027	HENDD	05027	HFSTD	05027	WF650	860	2	Low
Antique Elm Cherry	07	HQRTA	05163	HREDD	05163	HTMDA	05163	HENDD	05163	HFSTD	05163	WF651	860	2	Low
Antique Elm Natural	08	HQRTA	05052	HREDD	05052	HTMDA	05052	HENDD	05052	HFSTD	05052	WF648	860	3	Med/Low
African Ebony Natural	09	HQRTA	05054	HREDD	05054	HTMDA	05054	HENDD	05054	HFSTD	05054	WF656 WF656	1630	4	Medium
Brazilian Tigerwood Natural	12	HQRTA	05077	HREDD	05077	HTMDA	05077	HENDD	05077	HFSTD	05077	WF638	2160	5	Med/High
African Padauk Natural	13	HQRTA	05056	HREDD	05056	HTMDA	05056	HENDD	05056	HFSTD	05056	WF638	1800	4	Medium
<b>Australian Cypress Natural</b>	<b>15</b>	<b>HQRTA</b>	<b>05048</b>	<b>HREDD</b>	<b>05048</b>	<b>HTMDA</b>	<b>05048</b>	<b>HENDD</b>	<b>05048</b>	<b>HFSTD</b>	<b>05048</b>	<b>WF626</b>	<b>510</b>	<b>6</b>	<b>Med/High</b>

**Dropped**

## PRODUCT SPEC SHEET



Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch.

**PRODUCT SPEC SHEET**