



**Product Name & Number:** Brandy mill – WEC52 - 32352  
**Collection:** Artiquity  
**Construction:** Engineered – Scraped and Chattered  
**Face Genus / Species:** Maple (Acer spp), Hickory (Carya spp), Walnut (Juglans) and Ash (Fraxinus)  
**Core Species:** Poplar / Gum  
**Number of Plies:** 5  
**Product Thickness:** 3/8”  
**Width:** 5”  
**Grade:** Vintage  
**Edge / End:** Beveled / Eased  
**Face Finish:** Aluminum Oxide-Scraped & Chattered  
**Gloss Level:** 20° + or - 5°  
**Sq. Ft. Per Carton:** 28.25  
**Sq. Ft. Per Pallet:** 1130  
**Cartons Per Pallet:** 40  
**Weight Per Carton:** 40 lbs  
**Weight Per Pallet:** 1638 lbs  
**Installation:** On, Above or Below Grade  
 Glue, Staple, Nail or Float  
**Warranties:** 25 years Residential  
 5 years Light Commercial  
**Janka Hardness:** Hickory = 1820/ Maple = 1450  
**Photo Sensitivity:** Hickory = 3 / Maple = 2  
**Character Variation:** Medium / High

Color Name	Color #	Quarter Round		Reducer		T-Molding		Baby Threshold		Stair Nosing	
		HQRTA	05187	HREDC	05187	HTMDA	05187	HENDD	05187	HFSTC	05187
Hickory Chestnut	01	HQRTA	05187	HREDC	05187	HTMDA	05187	HENDD	05187	HFSTC	05187
Maple Harvest	03	HQRTA	05193	HREDC	05193	HTMDA	05193	HENDD	05193	HFSTC	05193
Hickory Country Natural	10	HQRTA	05188	HREDC	05188	HTMDA	05188	HENDD	05188	HFSTC	05188
Hickory Chocolate	11	HQRTA	05189	HREDC	05189	HTMDA	05189	HENDD	05189	HFSTC	05189
Hickory Charcoal	18	HQRTA	05192	HREDC	05192	HTMDA	05192	HENDD	05192	HFSTC	05192
Hickory Autumn	30	HQRTA	05190	HREDC	05190	HTMDA	05190	HENDD	05190	HFSTC	05190
Hickory Saddle	40	HQRTA	05191	HREDC	05191	HTMDA	05191	HENDD	05191	HFSTC	05191
Toasted Ash	101	HQRTA	05197	HREDC	05197	HTMDA	05197	HENDD	05197	HFSTC	05197
Cocoa Walnut	102	HQRTA	05138	HREDC	05138	HTMDA	05138	HENDD	05138	HFSTC	05138

**Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.**

**All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.**  
**Janka Wood Hardness Scale is a good indicator of a wood species’ resistance to indentations, however all wood will dent and scratch**