



Product Name & Number: Hilea Uniclic 32355 – WEW02
Collection: Rarity
Construction: Solid
Face Genus / Species: Bamboo, Moso, Phyllostachys Pubescens
Core Species: N/A
Number of Plies: N/A
Product Thickness: 3/8”
Width: 4.84”
Grade: Grade A
Edge / End: Kissed / Kissed
Face Finish: Crystal Shield Aluminum Oxide
Gloss Level: 35° + or – 5°
Sq. Ft. Per Carton: 22.15
Sq. Ft. Per Pallet: 930.03
Cartons Per Pallet: 42
Weight Per Carton: 62.83
Weight Per Pallet: 2688.9
Installation: On or Above Grade
 Float / Glue
Warranties: 25 Year Residential / 3 Year Commercial
Janka Hardness: 2977
Photo Sensitivity: 4
Character Variation: Medium

06-29-11 Update

Color Name	Color #	Quarter Round 72"		Reducer 72"		T-Molding 72"		Baby Threshold 72"		Flush Stair Nosing 72"		Overlap Stair Nosing 72"		Wood Filler
		HQRTA	05219	HREDC	05219	HTMDA	05219	HENDD	05219	HFSTC	05219	HSTPC	05219	
Natural	10	HQRTA	05219	HREDC	05219	HTMDA	05219	HENDD	05219	HFSTC	05219	HSTPC	05219	WF626
Baked Natural	12	HQRTA	05218	HREDC	05218	HTMDA	05218	HENDD	05218	HFSTC	05218	HSTPC	05218	WF676
Warm Chocolate	11	HQRTA	05256	HREDC	05256	HTMDA	05256	HENDD	05256	HFSTC	05256	HSTPC	05256	WF651
Warm Cherry	16	HQRTA	05257	HREDC	05257	HTMDA	05257	HENDD	05257	HFSTC	05257	HSTPC	05255	WF638
Butter-scotch	22	HQRTA	05258	HREDC	05258	HTMDA	05258	HENDD	05258	HFSTC	05258	HSTPC	05258	

Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch