

JACOBEAN

Prep Sink / Bar Faucet

2470-5203

Features

- Solid brass construction
- Forged brass body
- Swivel spout assembly with side-mounted ADA compliant lever handle
- Independent rotational and pivoting lever handle elements
- Rotating spout assembly with integral supply hoses
- 7.73" (19.7 cm) spout height at outlet
- 6.70" (17.0 cm) spout reach (c-c)
- For single hole configurations
- ADA Complaint (Handles Only)
- 1.8 GPM (6.8 LPM) Max

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAMPO/cUPC
- NSF/ANSI/CAN 61, SECTION 9
- NSF/ANSI 372
- IPC
- ADA & ICC/ANSI A117.1 (Handle Only)
- Energy Policy Act of 1992
- California Energy Commission
- ASME A112.18.3 (Back Flow)
- All applicable US Federal and State material regulations

Colors / Finishes

• 10B: Oil Rubbed Bronze 15: Polished Nickel • 15S: Satin Nickel - PVD Polished Chrome

• Other: Refer to the Newport Brass catalog for additional color/finish options.



Specified Model		
Model	Description	Colors Finishes
2470-5203	Two-Handle Prep Sink / Bar Faucet	☐ 10B ☐ 15 ☐ 15S ☐ 26 ☐ Other

Product Specification Add "Color / Finish" suffix to Model number, below.

The Single-Handle Prep Sink / Bar Faucet shall be made of solid brass construction. Faucet shall feature brass body with integral supply hoses and feature single-handle operation of a side-mounted Euro-motion ceramic disc 35 mm valve cartridge. Faucet shall have a 1.8 gallon (6.8 liter) per minute maximum flow rate. Product shall accommodate single hole configurations. Product shall incorporate a 7.73" (19.7 cm) spout height at outlet and a 6.70" (17.0 cm) spout reach (c-c). Faucet shall incorporate an ADA compliant traditional lever handle. Prep Sink / Bar Faucet shall be Newport Brass Model 2470-5203/_

2470-5203

PRODUCT DIMENSIONS (Units are in inches)



