

• Quarter-turn washerless ceramic disc valve cartridge

• 1.5 gallons (5.7 liters) per minute maximum flow rate

• ADA compliant traditional hot lever handle • Spout assembly with integral supply hoses • Spring-loaded, normally closed lever handle

• 6-5/8" (16.8 cm) spout height at outlet

• 4-3/4" (12.1 cm) spout reach (c-c)

## **JACOBEAN**

### **Hot Water Dispenser Faucet**










# 2470-5613



#### Codes / Standards Compliance Meets or exceeds the following at date of manufacture:

• ASME A112.18.1/CSA B125.1


• For single hole configurations

• IAPMO/cUPC

**Features** 

• Solid brass construction

- IPC
- NSF 61
- ADA
- Energy Policy Act of 1992
- All applicable US Federal and State material regulations



#### Colors / Finishes

• 10B: Oil Rubbed Bronze • 15: Polished Nickel

• 15S: Satin Nickel

• 26: Polished Chrome

• Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model			
Model	Description	Colors / Finishes	
2470-5613	Hot Water Dispenser Faucet	□ 15 □ 15S □ 26 □ 10B	Other
5-036	Point-of-Use Water Heater (115V, 140iF to 190i range)		

#### **Product Specification:** Add "Color / Finish" suffix to Model number, below.

The Hot Water Dispenser Faucet shall be made of solid brass construction. Faucet shall incorporate a spout assembly with integral supply hoses and feature a quarter-turn washerless ceramic disc valve cartridge. Faucet shall incorporate an ADA compliant contemporary hot lever handle. Hot Water Dispenser Faucet shall have a 1.5 gallons (5.7 liters) per minute maximum flow rate and accommodate single hole configurations. Product shall incorporate a 6-5/8" (16.8 cm) spout height at outlet and a 4-3/4" (12.1 cm) spout reach (c-c). Hot Water Dispenser Faucet shall be Newport Brass Model 2470-5613/\_\_\_\_ . [Point-of-Use Water Heater shall be Newport Brass Model 5-036].

#### **Product Dimensions** (units are in inches)

