# **NuTone**

#### **DESCRIPTION**

#### LIGHT FIXTURE:

- · Corrosion resistant brushed nickel finish
- · Frosted glass shade
- · Close mount design
- Uses two 60 Watt maximum, candelabra base bulbs. Bulbs not included.
- · Vent openings in fixture base for exhaust fan
- · Light fixture assembly is plug-in and removable

#### BI OWER

- · Plug-in permanently lubricated motor
- · Polymeric blower wheel

#### HOUSING:

- Rugged, 26-gage galvanized steel construction
- Fits in 2" x 6" construction
- Sturdy key-holed mounting brackets for quick, accurate installation
- Tapered, polymeric duct fitting with built-in backdraft damper for easy, positive duct connection and no metallic clatter

DO NOT install in a tub or shower enclosure.

NOTE: For installation in flat ceilings only.

U.L. Listed for use in insulated ceilings (Type I.C.)

Use supply wiring rated for at least 90° C


#### **SPECIFICATIONS**

VOLTS	AMPS	CFM	SONES	DUCT
120	1.6	70	2.0	4" Round




HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.





## Decorative Ventilation Fan with Light

### **MODEL 745BNNT**



#### ARCHITECT'S SPECIFICATION

Decorative Ventilation Fan with Light shall be NuTone Model 745BNNT.

Unit shall have galvanized steel housing with dual integral mounting brackets. It shall be ducted to a roof or wall cap.

Blower assembly shall be removable and have a permanently lubricated motor.

Light fixture assembly shall be plug-in, removable and include a frosted glass shade and a corrosion-resistant base with brushed nickel finish.

Lamps shall be two 60 Watt maximum, candelabra base, incandescent.

Air delivery to be no less than 70 cfm and sound level no greater than 2.0 sones. Air and sound ratings shall be certified by HVI. Unit shall be U.L. Listed for use in insulated ceilings (Type I.C.)

## INSTALLATION

Complete installation instructions are included with each Decorative Ventilation Fan with Light.

Broan-NuTone LLC Hartford, Wisconsin www.nutone.com 888-336-3948

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date

11K 99044761A