

INSTALLATION MANUAL

LED 11" Flush Mount Light

important safety instructions



Thank you for purchasing our product. The device has been manufactured from components with advanced optoelectronics to ensure high reliability and long performance. Before assembling please read carefully this Operation Manual and save in the safe place for future reference. Please note that all electrical connections must be in accordance with local and National Electrical Code standards as well as local building code, in case you are not familiar with proper wiring connections and buildin code consult a qualified electrician.

Technical Data

MODEL:	62/795
Power consuption:	12.5W
Pupil lumens :	720 lumens
Input Voltage:	120V/277V
Color temp.:	3,000K
Life span:	40,000h

Illumination authorization <5% per 10,000h



National Toll-Free:

Corporate Offices: 800,43,SATCO 110 Heartland Blvd. (800.437.2826) Brentwood NY 11717 www.satco.com 800.437,2826 631,243,2022 Fax 631.243.2027



DANGER - RISK OF SHOCK - DISCONNECT POWER BEFORE INSTALLATION AVANT L'INSTALLATION OU LA MISE EN SERVICE, débranchezi'alimentationélectrique

WARNING "THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION. CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED, "RISQUE D'ÉLECTROCUTION - LE PRODUIT DOIT ÊTRE INSTALLÉ EN CONFORMITÉ AVEC LE MODE D'INSTALLATION par une personne ayant les connaissances requises dans le domaine des risqueset dispositions mentionnées ci-dessus, AVANT L'INSTALLATION OU LA MISE EN SERVICE. débranchez alimentationé lectrique par l'INTERRUPTEURoudébranchez la prise.

Installed per local building codes

lesconnexionsélectriquesdoiventêtreconformes au Code des NormesÉlectriques locales et nationales

et au Code du Bâtiment local. -Risk of fire or electric shock.

-RISQUE D'ÉLECTROCLITION

-For use in dry and damp location.

-Pour emplacement sec et humide

-To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects, Pour empêcher les dommagesoulabrasion, n'exposez pas le câblage aux bords de la fôleoud'autresobjets

DIMMING

This product is compatible with most residential type dimmers available on the market. The dimming performance will depend on kind of dimmer and dimmer settings. Visit Satco.com for an up to date list of compatible

CLEANING AND STORAGE

- . Clean with a soft or damp cloth, While cleaning with the damp cloth make sure the power is off,
- . Do not clean with liquids or abrasives.
- Store at ambient temperature maximum 60°C.

5 YEAR LIMITED WARRANTY

The purchased product is covered with 5 year (60 months) augrantee in respect of any defect in material or workmanship after purchase date.

SATCO shall bear no responsibility on account of guarantee, as well as shall bear no liability for any faults, in case of improper operation, use, nealigence, accident or exposure to natural hazard, or excessive use over the limits specified for the unit, or if any unauthorised alteration or repair fol-

INSTALLATION (Four simple steps,)



Attach installation bracket to junction box by two screws (provided)



Connect AC cables from junction box and from light fixture with orange wire connectors(provided)



Attach base of fixture to mounting bracket using two nuts(provided)



Alian slots on the cover with the tabs in the base and twist