



OXYGEN LIGHTING ©

CRESCENT vanity
 120v **3-582-14**
 277v **37-582-14**

- | | | | | |
|--|--|--|---|---|
| <p>LAMPING</p> <ul style="list-style-type: none"> <input type="checkbox"/> (2x) 10.1w LED array <input type="checkbox"/> 3000K, 350mA (ea.) <input type="checkbox"/> Initial Lumens: 2920 lm <input type="checkbox"/> Delivered Lumens: 1982 lm <input type="checkbox"/> CRI>80 <input type="checkbox"/> Color Consistency: 3 Step MacAdam Ellipse | <p>DRIVER (Dimmable)</p> <ul style="list-style-type: none"> <input type="checkbox"/> (2x) 0-10v & Reverse Phase Dimming Constant Current, 12w, 350mA | <p>METAL FINISHES</p> <ul style="list-style-type: none"> <input type="checkbox"/> 14 - Polished Chrome <input type="checkbox"/> 24 - Satin Nickel | <p>DIMENSIONS</p> <ul style="list-style-type: none"> <input type="checkbox"/> 30.50" (w) x 3.50" (h) x 3.00" (ext.) | <p>INSTALLATION</p> <ul style="list-style-type: none"> <input type="checkbox"/> 2" x 3" J-Box <input type="checkbox"/> ETL Dry/Damp Listed <input type="checkbox"/> ADA <input type="checkbox"/> Conforms to UL STD 1598 Certified CAN/CSA STD C22.2 No. 250.0 |
| <p>INPUT VOLTAGE</p> <ul style="list-style-type: none"> <input type="checkbox"/> 120v OR 277v 50/60Hz | <p>DIFFUSER</p> <ul style="list-style-type: none"> <input type="checkbox"/> Matte White Acrylic | | | |

Oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

Sample Catalog Number			
Series #	Finish	=	Catalog Number
3-582	24		3-582-24
PROJECT: _____			
DATE: _____			

