Pamex Locks

Troy FHS Series

FEATURES & OPTIONS

Door Prep.

Cross Bore: 2-1/8", Edge: 1" Center to Center: 5-1/2"

Interior Trim FT3-Saturn knob interior trim

(other options available)

Latch Backset

Deadbolt: 2-3/8" deadbolt standard Handle: 2-3/8" plainlatch standard (other options available)

Faceplate

1" x 2-1/4" round corner standard (other options available)

Bolt

Deadbolt: 1" throw Lever: 1/2" throw

Door Thickness

Fit 1-3/8" to 1-3/4" standard (extension kit available for 1-3/4" to 2-1/4" door)

Cylinder

5-pin KW keyway solid brass cylinder standard 5-pin SC "C" keyway available

Strike Plate

Deadbolt: 2-1/4" x 1-3/4" full lip round corner standard Handle: 2-1/4" x 1-3/4" full lip round corner standard (other options available)

Handing Specify handing when order lever interior trim

ANSI/BHMA

A 156.2 Grade 3

FINISHES

(other finishes available upon request with lead-time)

□ US10B – 613 – Oil Rubbed Bronze

- □ US15 619 Satin Nickel
- □ US26 625 Polished Chrome

WARRANTY

- Lifetime mechanical warranty
- · Five years finish warranty

FUNCTIONS

Single Cylinder – FHS1

Deadbolt operated by key outside and turnpiece inside. Latchbolt operated by thumb-piece outside and knob or lever inside.

Double Cylinder – FHS2

Deadbolt operated by key on both sides. Latchbolt operated by thumb-piece outside and knob or lever inside.

Dummy – FHS4

Handle and knob or lever act as pull only. No operation.







