


4 Function Handheld



- | | |
|--|--|
| LG16-510B Finish(B) <input type="checkbox"/> | LG16-510D GFinish(DG) <input type="checkbox"/> |
| LG16-510BG Finish(BG) <input type="checkbox"/> | LG16-510GS Finish(GS) <input type="checkbox"/> |
| LG16-510C Finish(C) <input type="checkbox"/> | LG16-510K Finish(K) <input type="checkbox"/> |
| LG16-510D Finish(D) <input type="checkbox"/> | LG16-510SDB Finish(SDB) <input type="checkbox"/> |
| | LG16-510Y Finish(Y) <input type="checkbox"/> |

Specifications

Features

- 1.75 GPM Flow Rate
- Handheld Only
- Easy to Clean Nozzles
- 4 Function Handheld: Full Spray, Full Spray/Massage Combo, Massage, and Pause/Non-Positive Shut-Off
- Limited Lifetime Warranty

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
 - ASME A112.18.3 (Backflow Prevention)
- EPA WaterSense Certified
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1



Dimensions

