PF9400 Series

High-Efficiency Toilet Vitreous China - 1.28gpf



Product Features

- Two-piece vitreous china
- 1.28 gpf HET, High Efficiency Toilet
- High Performance 3" Flush Valve
- 2" glazed trapway
- · Gravity fed, double jetted box rim
- EPA WaterSense Certified

- Meets ANSI ASME A112.19.14-2006 and ASME A112.19.2M
- 8-1/2" x 7" water surface
- Available in round, elongated and ADA
- Close coupled tank with cover
- Seat and supply not included
- Uses 20% less water than standard low consumption toilets
- · Anti-siphon fill valve available
- Chrome tank lever standard



PF9401/PF9412

Model Numbers

PF9400WH 1.28 gpf round front bowl white PF9401WH 1.28 gpf elongated bowl white PF9403WH 1.28 gpf ADA bowl white

PF9412WHC 1.28 gpf HET tank white w/chrome trip lever

PF9412RWH 1.28 gpf RH tank white

PF9400BS 1.28 gpf round front bowl bisc PF9401BS 1.28 gpf elongated bowl bisc PF9403BS 1.28 gpf ADA bowl bisc PF9412BS 1.28 gpf tank bisc

PF9410WH 1.28 gpf tank for 10" rough white **PF9414WH** 1.28 gpf tank for 14" rough white

PF9412UWH 1.28 gpf lined tank white

PF9412LWH 1.28 gpf tank with locking lid white

Available Parts

PF9412FLPK Fill valve assembly
PF9412FRPK 3" Replacement flapper
PF9412FVPK 3" Flush valve assembly
PF9412TGPK Tank gasket w/bolts
PF9412LIDWH Tank lid white

PF9412TLCP Replacement chrome trip lever

Optional Accessories

MB130962 FLUSH LEV F/ 9400 HET CLST BN
MB130964 FLUSH LEV F/ 9400 HET CLST ORB
MB130960 FLUSH LEV F/ 9400 HET CLST CP

Warranty and Codes

This product comes complete with installation, operating, care and maintenance instructions. All PROFLO fixtures carry a 1-year limited warranty. In an effort to continually improve our products, we will make design changes from time to time. We reserve the right to ship newly designed product to fill any order unless we agree









PF9400 Series

High-Efficiency Toilet Vitreous China - 1.28gpf



Certifications

Meets strict flushing performance guidelines established by the EPA (Environmental Protection Agency) WaterSense program. Leadership in Energy and Environmental Design (LEED) Compliant. Los Angeles Department of Water and Power (LADWP) Compliant.

| | PF9412/ PF9400 | PF9412/ PF9401 | PF9412/ PF9403 |
|---|-------------------|-------------------|-------------------|
| Α | 28" | 29-1/2" | 29-1/2" |
| В | 16-1/2" | 18-1/2" | 18-1/2" |
| C | 16-1/8" | 16-1/8" | 17" |
| D | 30-1/8 | 30-1/8 | 31" |
| E | 8-3/8" | 8-3/8" | 8-3/8" |
| F | 12" | 12" | 12" |

| | PF9410/ PF9400 | PF9410/ PF9401 | PF9410/ PF9403 |
|---|-------------------|-------------------|-------------------|
| Α | 26-3/8" | 28" | 28" |
| E | 6-3/4" | 6-3/4" | 6-3/4" |
| F | 10" | 10" | 10" |

| | PF9414/ PF9400 | PF9414/ PF9401 | PF9414/ PF9403 |
|---|-------------------|-------------------|-------------------|
| Α | 29-1/2" | 31-1/2" | 31-1/2" |
| E | 10" | 10" | 10" |
| F | 14" | 14" | 14" |

Footprint

| | RF | EL | ADA |
|---|----------|----------|----------|
| | PF9400 | PF9401 | PF9403 |
| G | 19-1/2" | 18-3/16" | 19-1/2" |
| Н | 5-13/16" | 5-13/16" | 5-15/16" |
| ı | 5-15/16" | 5-1/2" | 6" |
| J | 9-5/8" | 9-1/2" | 10" |











