

Project:			
Fixture Type:			
Location:			
Contact:			

P2321 Series

LED Flush Mount • Damp Location



Specifications:

Description:

The P2321 features a 120V alternating current (AC) source which eliminates the need for a traditional LED driver.

Construction:

- · Etched Umber glass bowl -9" dia.
- · Painted Antique Bronze (-20)
- Steel construction
- LED Module is replaceable (part # 93053641)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- · Covers a standard 4" recessed outlet box
- · Mounting strap for outlet box included

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens	1211 (LM-79)
CCT	3000K
CRI	90
LPW	71
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 yrs.
Labels	cCSAus certified for damp locations ENERGY STAR® qualified

P2321-2030K9


Images:





Dimensions:

Α	В	
11"	4"	



Catalog number:

Base	Base Finish	Color Temp	CRI
P2321	20 - Antique Bronze	30K - 3000K	9 - 90 CRI



P2321 Series

LED Flush Mount • Damp Location



P2321-2030K9

Dimming Notes:

P2321 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.