

roject:	
xture Type:	
ocation:	
ontact:	

LED FLUSH

Ceiling mounted · Wet location listed





Specifications:

Description:

The all-in-one LED Surface Mount/recessed trim uses an intuitive snap-in system that allows easy flush mount installation to a junction box. 7-1/4" round 3000K, 1050 lumens, 90+ CRI. Dimming with many TRIAC dimmers. Wet location listed.

Construction:

Antique Bronze (-20) Steel construction

Glass: White polycarbonate lens

Flicker-free dimming to 10% brightness with most ELV type dimmers

(See Dimming Notes)

Title 24 compliant

covers a standard 4" hexagonal recessed outlet box

Mounting strap for outlet box included

6" of wire supplied

Antique Bronze finish

Flicker free dimming down to 10%

Intuitive snap-in system

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	
Input Frequency	
Lumens/LPW	1050/63 (LM-79) per module
CCT	3000K
CRI	
Life	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR® qualified

P8022-20-30K

Images:



Dimensions:

Diameter: 7-1/4" Height: 1-1/4"

Catalog number:

 Base
 Finish
 Color Temp
 CRI

 P8022
 20 - Antique Bronze
 / 30K - 3000K
 Blank- 90 CRI