

KISS LED

Ceiling stem mount • Dry location listed



Specifications:

Description:

Modern LED mini-pendant with sleek lines. 120V AC replaceable LED module, 623 lumens, 3000K color temperature and 90+ CRI.

Construction:

- Brushed Nickel (-09) (plated)
- Steel construction metalLED Module is replaceable (part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- Title 24 compliant
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- Ten feet of wire supplied

Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Dry location listed ENERGY STAR® qualified

P5186-0930K9

Images:



Dimensions:

Diameter: 5"
Height: 5-7/8"
Overall ht. w/stem: 72"

Catalog number:

Base	Finish	Color Temp	CRI
P5186	09 - Brushed Nickel	30K - 3000K	9 - 90 CRI

P5186-0930K9

Dimming Notes:

P5186 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.