

LED ALABAS-

Ceiling mounted • Damp location listed



Specifications:

P350003-009-30

Description:

One-light DC LED Flush Mount

Construction:

- Brushed Nickel (-009)
- Steel construction
- Glass: Etched Alabaster glass bowl
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Brushed Nickel finish
- 120V AC replaceable module
- Dimmable to 10% with Triac or ELV dimmers
- 3000k color temperature
- TM-21 60,000 hour life

Performance:

Number of Modules	1
Input Power	28W
Input Voltage	120V
Input Frequency	
Lumens/LPW	1416/50.57142857 (LM-79) per module
CCT	3000K
CRI	
Life	(L70/TM-21)
EMI/RFI	FCC Title 47 Part 158 Class B, ICES-003 Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	ETL Damp location listed ENERGY STAR® qualified

Images:



Dimensions:

 Diameter: 15"
 Height: 6-3/4"

Catalog number:

Base	Finish	Color Temp	CRI
P350003	009 - Brushed Nickel	30	Blank- 90 CRI