


# Compact fluorescent

# **Step Light**Indoor & Protected Outdoor Non-IC

D	_	-	٠.	c	^	٦	
ĸ	е	CE	36	5	е	а	

Type			
	-30		
P6821			

	Finish			Dimensions (Inches)		
Catalog No.	White	Lamping	Α	В	С	
P6821	-30	1-7w or 9w CF	8-5/8	5-7/8	3-1/2	
			Wall Opening = $5 \times 7-5/8$			



## **Specifications:**

#### Face Plate

- White powder coated steel
- Louver has linear baffles to direct all light downward
- Gasketed for light leak prevention
- Both fasten to housing with torsion springs

#### **Housing**

- White steel
- Interior wiring compartment
- Two 1/2" KO's for wiring
- For indoor and protected outdoor use
- Units must be mounted at least 3" from any insulation
- Mounting clips for direct mounting to wall board are provided
- Housing has brackets to accept P8716-01 hanger bars, if required

#### Electrical

- 120v NPF magnetic ballast
- G23 base lampholder
- Multiple units can be wired together without the need of separate junction boxes
- Minimum start temperature

7w -0° F

9w +32° F

### Labeling

• UL-CUL damp location listed

Progress Lighting 701 Millennium Blvd. Greenville, South Carolina 29607