Incandescent

Cylinders Surface Mount

Outdoor



| | Finish | | | | Dimensions (Inches) | |
|-------------|--------|-------|-------|------------------|---------------------|----|
| Catalog No. | Bronze | White | Black | Lamping | Α | В |
| P5741 | -20 | -30 | -31 | 250PAR38/150BR40 | 6 | 12 |
| | | | | | | |
| | | | I | | | |
| | | | - | — A — | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | В | | | |

Specifications:

<u>General</u>

- Extruded aluminum .125 wall thickness
- Ceiling or pendant mounted
- Powder coat Bronze (-20), White (-30) or Black (-31) finishes
- Interior finish matches exterior finish

Mounting

- Ceiling mount
- Covers any outlet box
- Mounting hardware included
- Pendant mount
- Order pendant kit (P8741) separately
- Pendant kit includes canopy, hang straight swivel and 6" and 12" stems with coupling

<u>Electrical</u>

 Medium base porcelain socket with nickel plated brass screw shell

<u>Labeling</u>

• UL-CUL wet location listed

Progress Lighting 701 Millennium Blvd. Greenville, South Carolina 29607 www.progresslighting.com