



# L-Series

Commercial Locks



# Contents

5	L-Series Commercial Locks
7	Schlage L9000 Series
7	Schlage L400 Series
8	Danmark Levers
12	Lever Designs and Finishes
18	Escutcheons and Roses
19	Thumbturns
20	Lock Components
21	Lock Functions - ANSI A156.13, Series 1000
22	Lock Functions - Single Cylinder Non-Deadbolt
23	Lock Functions - Single Cylinder Deadbolt
24	Lock Functions - Double Cylinder Non-Deadbolt and Deadbolt
25	Lock Functions - Full Mortise and Small Mortise Deadlocks
26	L-Series Universal Transformation Instructions
28	Electrified Lock Function
29	Cylinder Types
30	Standard (Non-IC) Cylinders
31	Full-Size Interchangeable Core (FSIC) Cylinders
32	Small Format Interchangeable Core (SFIC) Cylinders
33	Blocking and Compression Rings
34	Classroom Thumbturn Cylinders
35	Armored Fronts
36	Strikes
37	Door Handing
38	Specifications
38	Certifications



Be sure to ask your SSC representative to tell you about **Custom Solutions** by Ingersoll Rand Security Technologies. To learn more visit [securitytechnologies.ingersollrand.com](http://securitytechnologies.ingersollrand.com).



**Quiet**Solutions



**Custom**Décor



**High**Security and Safety



**Environmental**Solutions



**Flexible**Configurations



## Put Your Trust in the Name You Know

For more than 90 years Schlage<sup>®</sup> has been providing innovative security solutions for schools, hospitals, hotels, condominiums and a host of other commercial buildings. Today, Schlage is at the forefront of cutting-edge technology including wireless security, access control systems including readers, credentials and biometrics. With a wide range of products, styles and finishes, Schlage has what you need no matter how demanding your project specifications may be. And, we stand behind every product we make with the best after-sales service in the business. It's this commitment to design, performance and technology that ensures you can stand behind our products too.



## Real Security is Knowing Exactly What You Want and Getting It

When you know exactly what you want, you don't want to waste time finding out whether it meets your project specifications. That's why we offer the world's largest team of hardware specification writers to help you and your clients turn your vision into reality. And when it comes to products, our commercial suiting options, wide variety of lever designs and rich selection of finishes give you the tools you need to make your projects perfect. You know what you want. With Schlage you can be sure you'll get it.

### **Safety, Security and Confidence**

When you choose a Schlage lock you can be sure you've done the job right the first time. After all, our products are among the most durable and dependable on the market today. Our locks are easy to install, and simple to repair and maintain. That means fewer callbacks for you and total safety and security for your customers.



# L-Series

## Commercial Locks

### **Nothing is tougher.**


At Schlage we know that every product you specify has to stand up to constant use and abuse. Your building's locking systems face an additional challenge – keeping people and other assets safe while delivering constant, reliable performance. Schlage L-Series Extra Heavy Duty Mortise Locks are built to withstand the rigors of daily use without fail.

### **We don't compromise on security.**

The safety and security of your clients' buildings is something we take very seriously. That's why every Schlage lock and deadbolt undergoes intensive testing to determine its ANSI grade level:

- Cycle tests
- Door impact tests
- Bolt strength tests
- Resistance tests
- Warped door tests

We pay attention to these details so you can focus on creating a functional and aesthetically pleasing environment for your clients. In fact, every one of our L-Series locks meets ANSI Grade 1 standards for safety.



## Vandlgard®

The L-Series Vandlgard is ideal for areas subject to abuse or anywhere vandalism is likely to be present. Vandlgard prevents damage to internal lock components caused by excessive force from kicking, hitting or standing on the lever to gain access.

It's easy to retrofit standard L-Series locks with Vandlgard using the Vandlgard Retrofit Kit.

# The Right Lock for Every Application

## Schlage L9000 Series

Our L9000 Series locks are ideal for use in schools, hospitals and factories, where the finest hardware must also deliver consistent, dependable operation and stand up to constant use and abuse.

### Strength and Durability


1. Fully wrapped heavy-gauge steel case protects against door edge attacks
2. All-metal zinc dichromate-plated working parts
3. Inside lock case protects electronic components
4. Two-piece anti-friction tongue reduces wear and tear
5. Outside and inside trim thru-bolted together and through the door

### Security Built In

6. Break-away spindle prevents unsecured failures and provides easy spindle replacement
7. Hub blocking plate protects lock against spindle manipulation
8. Spring-loaded fusible link provides fail secure mode in case of fire
9. Inside lever applied by screwless shank mounting – no exposed trim mount screws

### Adaptable To Your Application

10. Universal lock case – ten functions in one case
11. Floating mounting tabs automatically adjust to fit a beveled door edge
12. Field-reversible handing without opening lock case
13. External spring cages allow for simple trim retrofit
14. Locking thumbturn on the inside of door visually shows when the door is locked and unlocked
15. Lever rotation in both directions (up and down) for ease of use
16. Independent lever rotation



## Schlage L400 Series

Our L400 Series locks are designed for use as primary locks where no latching is required, such as restrooms and small doors to utility spaces. They also offer optimum security when used as auxiliary locks in other applications.

1. High-strength steel alloy cylinder retainer
2. Armored front in brass, bronze or stainless steel; adjustable for door bevel
3. 1" (25 mm) stainless steel throw deadbolt
4. Deeper retainer groove in cylinder shell increases security against wrenching and pullout; all cylinders backward compatible
5. 6-pin Everest 29™ cylinder with patented keys standard
6. Steel case and parts are corrosion resistant

# danmark levers

## **Designed by architects for architects.**

Introducing danmark by Schlage, a sleek, contemporary lever line with a distinctively European influence. Crafted with simplicity and flexibility in mind, danmark levers are pleasing to the eye and the touch, and allow the architect to express their vision down to the very last detail.



## Great ideas deserve danmark.


All danmark levers are built using the best materials, like solid stainless steel that easily withstands repeated use. Because they are backed by Schlage, danmark levers can be relied on to provide superior performance and security.

- Constructed of solid stainless steel
- Designed for use with L-Series extra heavy duty mortise locks
- Exceeds ANSI A156.12, 1994, Grade 1 locked lever torque requirements
- All levers available in satin stainless steel finish (630) only

## danmark Lever Designs

615

**Material:** Cast stainless steel



621

**Material:** Cast stainless steel




695

**Material:** Cast stainless steel



615

**Material:** Cast stainless steel



690

**Material:** Cast stainless steel




## Finish Key



630  
Stainless Steel



660  
**Material:** Cast stainless steel




650  
**Material:** Cast stainless steel



696  
**Material:** Cast stainless steel



640  
**Material:** Cast stainless steel



# High Performance Meets High Style

Bright and brushed finishes in brass, bronze, chromium, stainless steel and more. Knobs or levers. Sleek sophistication or classic elegance. The Schlage L-Series collection offers the choices you need – and a few that might surprise you.

## Lever Designs and Finishes



01

**Material:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



03

**Material:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



02

**Material:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



05

**Material:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e





06

**Material:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



07

**Material:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



12

**Materials:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e  
 Specify door hand



## Finish Key\*



605  
Bright Brass



606  
Satin Brass



609  
Antique Brass



612  
Satin Bronze



613  
Oil Rubbed Bronze



619  
Satin Nickel



625  
Bright Chromium Plated



626  
Satin Chromium Plated



626AM  
Antimicrobial Coating on  
Satin Chromium



629  
Bright Stainless Steel



630  
Satin Stainless Steel



630AM  
Antimicrobial Coating on  
Satin Stainless Steel



643e  
Aged Bronze

## Lever Designs and Finishes



17

**Material:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



Latitude

**Material:** Forged brass and cast stainless steel  
**Finishes:** 605, 619, 625, 626, 629, 630, 643e



18

**Material:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



Longitude

**Material:** Forged brass and cast stainless steel  
**Finishes:** 605, 619, 625, 626, 629, 630, 643e



Omega (OME)

**Material:** Forged brass, bronze and cast stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



SL1 - Anti-Ligature


**Material:** Cast Stainless Steel  
**Finish:** 630






**ASTI (AST)**

**Material:** Forged brass  
**Finishes:** 605, 619, 625, 626, 643e



**Accent (ACC)**

**Material:** Forged brass  
**Finishes:** 605, 619, 625, 626, 643e



**41 Orbit (ORB)**

**Material:** Heavy wrought brass, bronze or stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



**Merano (MER)**

**Material:** Forged brass  
**Finishes:** 605, 619, 625, 626, 643e




**42 Plymouth (PLY)**

**Material:** Heavy wrought brass, bronze or stainless steel  
**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



**St. Annes (STA)**

**Material:** Forged brass  
**Finishes:** 605, 619, 625, 626, 643e



**SK1 - Anti-Ligature**

**Material:** Cast Stainless Steel  
**Finish:** 630



# Schlage Commercial Lever Suites

Whether you're choosing a lock system for a perimeter entry or common area, or handle sets for interior use, our Schlage Commercial Lever Suites let you create exactly the environment you want, while meeting strict standards for safety, security and performance.

## Commercial Suites



L06



ND Rhodes



AL Saturn



S Saturn



F Elan



L17



ND Sparta



AL Neptune



S Neptune



L07



ND Athens



AL Jupiter



S Jupiter



F Jazz



L Omega



ND Omega



AL Omega



L03



ND Tubular

## Multi-Family/Hospitality Suites



L12



F Manhattan



L Merano



FA Merano



L Accent



F Accent



L Asti



S Flair



F Flair



L St. Annes



FA St. Annes

## Finish Key\*



605  
Bright Brass



606  
Satin Brass



609  
Antique Brass



612  
Satin Bronze



613  
Oil Rubbed Bronze



619  
Satin Nickel



625  
Bright Chromium Plated



626  
Satin Chromium Plated



626AM  
Antimicrobial Coating on  
Satin Chromium



629  
Bright Stainless Steel



630  
Satin Stainless Steel



630AM  
Antimicrobial Coating on  
Satin Stainless Steel



643e  
Aged Bronze

\* Finishes not available in every lock series.  
Refer to pricebook for finish availability.

# Escutcheons and Roses

Choose from three types of escutcheon and two rose sizes to add tough, durable performance to your lockset.

## Escutcheons



### L Full Face

**Material:** Cold-forged brass, bronze or stainless steel

**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e

**Size:** 8" x 1 3/4" x 7/16"  
(203 mm x 44 mm x 11mm)



### L Concealed

**Material:** Cold-forged brass, bronze or stainless steel

**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e

**Size:** 8" x 1 3/4" x 7/16" (203 mm x 44 mm x 11 mm)



### N Escutcheon

**Material:** Heavy wrought reinforced brass, bronze or stainless steel

**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e

**Size:** 8" x 2 9/16" x 7/16"  
(203 mm x 65 mm x 11 mm)



## Roses



### A Wrought Rose

2 1/8" (54 mm) diameter  
Available for use on L-Series knob and lever designs.

Order by letter designation corresponding to the design and diameter desired.

**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e



### B Wrought Rose

2 9/16" (65 mm) diameter  
Available for use on L-Series knob and lever designs.

Order by letter designation corresponding to the design and diameter desired.

**Finishes:** 605, 606, 609, 612, 613, 619, 625, 626, 629, 630, 643e

# Thumbturns

Choose from three variations of thumbturn locks that help you meet the demands of specialized commercial projects.



**Hotel Occupancy Indicator**  
09-611  
For lock function L9486P, this unit can be used with A or B roses. Requires a 13/8" (35 mm) cylinder for 13/4" (44 mm) doors. Specify finish when ordering separately. Specify L583-575 for "OCCUPIED" message.



**Optional EZ Turn**  
L583-363  
Available for rose and escutcheon trim. Disability turn (ADA) option to standard thumbturn. Can be used with thumbturn-function L-Series lock except L9463 and L463. Specify lock per L583-363 when ordering.



**Coin Turn**  
For lock functions L9044 and L9444 with rose trim. Specify 09-509 and finish per L283-124 when ordering.



03 Lever Shown

**Products featuring a knurled surface will be indicated by adding the prefix "8" to the lever number. For example, L9050P 803A/03A.**


## Tactile Warning (Knurling)

Schlage L-Series commercial levers feature knurling only on the outside lever unless otherwise specified. This feature is available on the following lever models: 01, 03, 05, 06, 07, 12 and 17.


Tactile warning is applied to outside lever only unless otherwise specified.

# Lock Functions


## Lock Components



## Symbol Key



## Product Identification Guide



SFIC = Small Format (Best® style) Interchangeable Core

To order less Schlage logo, specify lock "with K510-612 faceplate."

LV = Vandlgard® function allows exterior lever to rotate freely down while remaining securely locked.

## Lock Functions | ANSI A156.13, Series 1000

Schlage      ANSI



**L9010**      **F01**  
**Passage Latch**

Latchbolt retracted by knob/lever from either side at all times. Inside lever is always free for immediate egress.



**L9040**      **F22**  
**LV9040**  
**Bath/Bedroom Privacy Lock**

Latchbolt retracted by knob/lever from either side unless outside is locked by inside thumbturn. Turning inside knob/lever or closing door unlocks outside knob/lever. To unlock from outside remove emergency button, insert emergency thumbturn (furnished) in access hole and rotate. Inside lever is always free for immediate egress.



**L9044**  
**LV9044**  
**Privacy With Coin Turn Outside**

Latchbolt retracted by knob/lever from either side unless outside is locked by inside thumbturn or outside coin turn. Operating inside knob/lever, closing door, rotating inside thumbturn or rotating outside coin turn unlocks outside knob/lever. Specify per L283-056 for Torx® screws. Available with rose trim only. (Previously XL11-868)



**L9440**      **F19**  
**LV9440**  
**Privacy With Deadbolt**

Latchbolt retracted by knob/lever from either side. Deadbolt thrown or retracted by inside thumbturn. Throwing deadbolt locks outside knob/lever. Rotating inside knob/lever simultaneously retracts deadbolt and latchbolt, and unlocks outside knob/lever. To unlock from outside remove emergency button, insert emergency thumbturn in access hole and rotate. Inside liner is always free for immediate egress. (Previously XL11-761.)

Schlage      ANSI



**L9444**  
**LV9444**  
**Privacy with Deadbolt and Coin Turn Outside**

Latchbolt retracted by knob/lever from either side. Deadbolt thrown or retracted by inside thumbturn or outside coin turn. Throwing deadbolt locks outside knob/lever. Rotating inside knob/lever simultaneously retracts deadbolt and latchbolt, and unlocks outside knob/lever. Rotating outside coin turn retracts deadbolt and unlocks outside knob/lever. Specify per L283-056 for Torx screws. Available with rose trim only. Inside lever is always free for immediate egress. (Previously XL11-868)



**L0170**  
**Half Dummy Trim**

Knob/lever on one side fixed by mounting bar.



**L0172**  
**Full Dummy Trim**

Knob/lever on both sides fixed by mounting bar.



**L9175**  
**Half Dummy Trim with Lock Case**

Fixed knob/lever on one side inoperable. Includes lock case and armored front. Options same as L9176 below.



**L9176**  
**Full Dummy Trim with Lock Case\***

Fixed knob/lever on both sides. Includes lock case and blank armor front. May be ordered with optional XL11-743 armored front with cutout to receive deadbolt.

\*In a double-door application where the dummy will be used as the strike order 10-091 Armored Front Strike separately.

## Lock Functions | Single Cylinder Non-Deadbolt Functions

Schlage ANSI



**L9050  
LV9050**

### Office and Inner Entry Lock

Latchbolt retracted by knob/lever from either side unless outside is made inoperative by key outside or by turning inside thumbturn. When outside is locked, latchbolt is retracted by key outside or by knob/lever inside. Outside knob/lever remains locked until thumbturn is returned to vertical or unlocked by key. Auxiliary latch deadlocks latchbolt when door is closed. Inside liner is always free for immediate egress.



**L9056  
LV9056**

### L9050 with Automatic Unlocking

Latchbolt retracted by knob/lever from either side unless outside is made inoperative by key outside or by rotating inside thumbturn. Outside knob/lever unlocked by key outside, thumbturn or closing door. Rotating inside knob/lever simultaneously retracts latchbolt and unlocks outside knob/lever. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress.



**L9070  
LV9070**

### Classroom Lock

Latchbolt retracted by knob/lever from either side unless outside is locked by key. Unlocked from outside by key. Inside knob/lever always free for immediate exit. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress.



**L9076  
LV9076**

### Classroom Holdback Lock

Latchbolt retracted by knob/lever from either side unless outside is locked by key. When locked, latchbolt retracted by key outside or knob/lever inside. Auxiliary latch deadlocks latchbolt when door is closed. Depress inside knob/lever and turn key 360° for holdback feature. Inside lever is always free for immediate egress.



**L9080  
LV9080**

### Storeroom Lock

Latchbolt retracted by key outside or by knob/lever inside. Outside knob/lever is always inoperative. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress.



**L9080EL  
LV9080EL**

### Electrically Locked (Fail Safe)

Outside knob/lever continuously locked by 24V AC or DC. Latchbolt retracted by key outside or by knob/lever inside. Switch or power failure allows outside knob/lever to retract latchbolt. Auxiliary latch deadlocks latchbolt when door is closed. Inside knob/lever always free for immediate exit. Inside lever is always free for immediate egress.

Schlage ANSI



**L9080EU  
LV9080EU**

### Electrically Unlocked (Fail Secure)

Outside knob/lever unlocked by 24V AC or DC. Latchbolt retracted by key outside or knob/lever inside. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress.



**L9080EL-RX / LV9080EL-RX  
L9080EU-RX / LV9080EU-RX**

### Request to Exit (RX) Electrified Lock

Same as L9080EL and L9080EU functions. In addition, a micro-switch positioned inside the lock case monitors the retractor crank, and is actuated when rotation of the inside or outside knob/levers rotates the retractor hub. The switch signals the use of that opening to security systems, allowing a non-disruptive means of immediate egress. Specify per L283-263 with L functions, specify L283-239 with LV functions. Inside lever is always free for immediate egress.

## Lock Functions | Single Cylinder Deadbolt Functions

Schlage      ANSI



**L9453**  
**LV9453**  
**Entrance Lock**

Latchbolt retracted by knob/lever from either side unless outside is locked by 20° rotation of thumbturn. Deadbolt thrown or retracted by 90° rotation of thumbturn. When locked, key outside or knob/lever inside retracts deadbolt and latchbolt simultaneously. Outside knob/lever remains locked until thumbturn is restored to vertical position. Throwing deadbolt automatically locks outside knob/lever. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress.



**L9456**  
**LV9456**  
**Corridor Lock**

Latchbolt retracted by knob/lever from either side. Deadbolt thrown or retracted by key outside or inside thumbturn. Throwing deadbolt locks outside knob/lever. Turning inside knob/lever simultaneously retracts deadbolt and latchbolt and unlocks outside knob/lever. Inside lever is always free for immediate egress.



**L9465**  
**Closet/Storeroom Lock**

Latchbolt retracted by knob/lever from either side. Deadbolt thrown or retracted by key outside.



**L9473**  
**F21**  
**Dormitory/Bedroom Lock**

Latchbolt retracted by knob/lever from either side. Deadbolt thrown or retracted by key outside or thumbturn inside.



**L9480**  
**LV9480**  
**Storeroom Lock With Deadbolt**

Latchbolt retracted by key outside or by lever or knob inside. Outside knob/lever always fixed. Deadbolt thrown or retracted by key outside or thumbturn inside. Turning inside knob/lever simultaneously retracts both deadbolt and latchbolt. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress. (Previously XL11-591)



**L9485 x XL11-557**  
**Prison Function Lock**

Latch retracted by key outside or knob inside. Outside knob always free spinning. Deadbolt only thrown or retracted by guard's key. Inside knob becomes fixed when deadbolt is thrown. Prisoner's key only retracts latchbolt. Furnished standard with tamper-resistant Torx screws. Specify per XL11-557.

Schlage      ANSI



**L9485**  
**LV9485**  
**Faculty / Hotel / Restroom Lock**

Latchbolt retracted by key outside or by knob/lever inside. Outside knob/lever always fixed. Deadbolt thrown or retracted by inside thumbturn. When deadbolt is thrown all keys become inoperative except emergency or display keys. Turning inside knob/lever retracts both deadbolt and latchbolt simultaneously. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress.



**L9486**  
**F15**  
**LV9486**  
**Faculty / Hotel / Restroom Lock**  
**"Do Not Disturb" Indicator**

Latchbolt retracted by key outside or by knob/lever inside. Outside knob/lever always fixed. Deadbolt thrown or retracted by inside thumbturn. When deadbolt is thrown "Do Not Disturb" plate is displayed. All keys become inoperative except emergency or display keys. Turning inside knob/lever retracts both deadbolt and latchbolt simultaneously. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress.



**L9486 x L583-375**  
**LV9486 x L583-375**  
**L9486 with "Occupied" Indicator**

Latchbolt retracted by key outside or by knob/lever inside. Outside knob/lever always fixed. Deadbolt thrown or retracted by inside thumbturn. When deadbolt is thrown "Occupied" plate is displayed and all keys become inoperative except emergency keys. Turning inside knob/lever simultaneously retracts both deadbolt and latchbolt. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress. (Previously XL11-580)



**L9496**  
**Privacy with "Occupied" Indicator**

Knob/lever retracts latchbolt from either side. Deadbolt thrown or retracted by key outside (retraction by key required in the event of an emergency) or inside thumbturn. Throwing deadbolt locks outside knob/lever and displays "Occupied" plate. Rotating inside knob/lever simultaneously retracts both deadbolt and latchbolt, and unlocks outside knob/lever. Inside lever is always free for immediate egress. (Previously XL11-885)

\*In a double-door application where the dummy will be used as the strike order 10-091 Armored Front Strike separately.

## Lock Functions | Double Cylinder Non-Deadbolt Functions

Schlage      ANSI



**L9060**  
**LV9060**  
**Apartment Entrance Lock**

Latchbolt retracted by knob/lever from either side unless outside is locked by key from inside. When locked, latchbolt retracted by key outside or knob/lever inside. Auxiliary latch deadlocks latchbolt when door is closed. Inside lever is always free for immediate egress.



**L9071**  
**LV9071**  
**Classroom Security Lock**

Latchbolt retracted by knob/lever from either side unless outside is locked by key from either side. When locked, latchbolt retracted by key outside or knob/lever inside. Auxiliary latch deadlocks latchbolt when door is locked. Inside lever is always free for immediate egress.



**L9077**  
**LV9077**  
**Classroom Security Holdback Lock**

Latchbolt retracted by knob/lever from either side unless outside is locked by key from either side. When locked, latchbolt retracted by key outside or knob/lever inside. Auxiliary latch deadlocks latchbolt when door is locked. Depress inside knob/lever and turn key 360° for holdback feature. Inside lever is always free for immediate egress.



**L9082**      **F30**  
**LV9082**  
**Institution Lock**

Latchbolt retracted by key from either side. Knob/lever on both sides always inoperative. Auxiliary latch deadlocks latchbolt when door is closed.



**L9082EL**  
**L9082EU**  
**L9082 Electrically Locked or Electrically Unlocked Both Sides\***

EL: Outside and inside knob or lever continually locked electrically. Latchbolt retracted by key either side. Switch or power failure allows outside and inside knob/lever to retract latchbolt. Auxiliary latch deadlocks latchbolt when door is closed. EU: Outside and inside knob/lever unlocked electrically. Latchbolt retracted by key either side. Switch or power failure keeps inside and outside knob/lever locked. Auxiliary latch deadlocks latchbolt when door is closed. (Previously XL11-452)

## Lock Functions | Double Cylinder Deadbolt Functions

Schlage      ANSI



**L9457**  
**LV9457**  
**Classroom Security Lock with Deadbolt**

Latchbolt retracted by knob/lever from either side. Deadbolt thrown or retracted by key from either side. Throwing deadbolt locks outside knob/lever. Turning inside knob/lever simultaneously retracts deadbolt and latchbolt, and unlocks outside knob/lever. Inside lever is always free for immediate egress.



**L9466**      **F14**  
**Store/Utility Room Lock with Deadbolt\***

Latchbolt retracted by knob/lever from either side. Deadbolt thrown or retracted by key from either side.



**L9482 x XL11-9543**  
**LV9482 x XL11-9543**  
**Institution Lock with Deadbolt\***

Latchbolt retracted by key from either side. Knob/lever on both sides always inoperative. Deadbolt thrown or retracted by key either side. Auxiliary latch deadlocks latchbolt when door is closed. Specify per XL11-543.

In a double-door application where the dummy will be used as the strike order 10-091 Armored Front Strike separately.

\*Caution: Double cylinder locks on residences and any door in any structure which is used for egress are a life safety hazard in times of emergency and their use is not recommended. Installation should be in accordance with existing codes only.

## Lock Functions | Full Mortise Deadlocks

	Schlage	ANSI
	<b>L9460</b>	<b>F17</b>
	<b>Cylinder x Thumbturn Lock</b> Deadbolt thrown or retracted by key outside or thumbturn inside.	
	<b>L9462</b>	<b>F16</b>
	<b>Double Cylinder Lock*</b> Deadbolt operated by key from either side.	
	<b>L9463</b>	
	<b>Classroom Lock</b> Deadbolt thrown or retracted by key from outside. Inside thumbturn cylinder retracts deadbolt, but cannot project it.	
	<b>L9464</b>	<b>F18</b>
	<b>Cylinder Lock</b> Deadbolt thrown or retracted by key from one side. No trim on opposite side.	
	<b>L9460 x XL11-635</b>	
	<b>L9460 with Pull</b> Knob/lever both sides fixed. Deadbolt thrown or retracted by key outside or thumbturn inside.	
	<b>L9460 x XL11-886</b>	
	<b>Single Cylinder Deadlock with Pull</b> Deadbolt thrown or retracted by key outside or thumbturn inside. No latch, but inside knob or lever is spring-loaded. Rotating inside knob/lever also retracts deadbolt. Fixed outside knob/lever.	
	<b>L9462 x XL11-886</b>	
	<b>Double Cylinder Deadlock with Pull*</b> Deadbolt thrown or retracted by key from either side. No latch, but inside knob/lever is spring-loaded. Rotating inside knob/lever also retracts deadbolt. Fixed outside knob/lever.	
	<b>L9464 x XL11-886</b>	
	<b>Deadlock with Pull</b> Deadbolt thrown or retracted by key from one side. No latch, but inside knob/lever is spring-loaded. Rotating inside knob/lever also retracts deadbolt. Fixed outside knob/lever.	

## Lock Functions | Small Mortise Deadlocks

	Schlage	ANSI
	<b>L460</b>	<b>E06071</b>
	<b>Cylinder x Thumbturn Lock</b> Deadbolt thrown or retracted by key outside or thumbturn inside.	
	<b>L462</b>	<b>E06061</b>
	<b>Double Cylinder Lock*</b> Deadbolt operated by key from either side.	
	<b>L463</b>	<b>E06091</b>
	<b>Classroom Lock</b> Deadbolt thrown or retracted by key from outside. Inside thumbturn cylinder retracts deadbolt, but cannot project it.	
	<b>L464</b>	<b>E06081</b>
	<b>Cylinder Lock</b> Deadbolt thrown or retracted by key from one side. No trim on opposite side.	
	<b>L480</b>	
	<b>Door Bolt</b> Deadbolt thrown or retracted by thumbturn from one side. No trim on opposite site.	
	<b>L496</b>	
	<b>Deadbolt with "Occupied" Indicator</b> Deadbolt thrown or retracted by key outside or thumbturn inside. When deadbolt is thrown "Occupied" plate is displayed. (Previously XL11-911)	




# Schlage L-Series Universal Transformation Instructions

The L9050 universal case can be transformed into nine different functions\* with just a few additional parts.

For some functions, additional parts are not necessary.

ANSI Function	Function Type	Function Description
F04	 L9050 (w/thumbturn) Office	Latchbolt operated by lever either side except when outside lever is made inoperative by a stop or other mechanical means other than key. When outside lever is locked, latchbolt is retracted by key from outside or by operating inside lever. Auxiliary deadlatch.
F01	 L9010 Passage	Latchbolt operated by lever from either side at all times.
F05	 L9070 Classroom	Latchbolt operated by lever either side except when outside lever is locked from outside by key or push button mechanism. When outside is locked latchbolt is retracted by key or by operating key or push button, and outside lever from outside or by operating inside lever. Auxiliary deadlatch.
F07	 L9080 Storeroom	Latchbolt operated by key outside or by operating inside lever. Outside lever always inoperative. Auxiliary deadlatch.
F09	 L9060 Apartment Entrance	Latchbolt operated by lever either side, except when made inoperative by key from inside. When outside is locked latchbolt is retracted by key from outside or by operating inside lever. Auxiliary deadlatch.
F31	 L9080 (less outside cylinder) Exit or Communicating	Latchbolt operated by inside lever. Non-removable blank trim or no trim outside.
F32	 L9071 Classroom Security	Latchbolt retracted by lever either side except when outside lever is locked by key from inside or outside. When outside lever is locked latchbolt is retracted by key either side or by inside lever. Auxiliary deadlatch.
	 L9080 (less outside lever) Service	Latchbolt operated by key outside or by operating inside lever. No outside lever. Auxiliary deadlatch.
	 L9080 (less inside trim) Utility	Latchbolt retracted by key outside; outside lever always inoperative. No inside trim. Auxiliary deadlatch.
	 L9070 (less inside trim) Closet	Latchbolt operated by lever on outside except when outside lever is locked from outside by key. When outside is locked latchbolt is retracted by key or by operating key from outside lever. Auxiliary deadlatch.

\* Assumes Everest 29™ cylinders and L9050 as base function (L283-133 Chassis/L9050LB Distributor Lock Case) — only applies to sectional trim (not escutcheon).

Transformation Instructions	Additional Part(s)	
Install cloverleaf cam cylinder on outside; install thumbturn assembly 09-509-027 on inside.	No additional parts required.	
Do not install thumbturn unit 09-509-027 on inside or cylinder outside. Install chassis in the unlocked position.	No additional parts required.	
Install cloverleaf cam cylinder on outside; do not install thumbturn assembly 09-509-027 on inside.	No additional parts required.	
Do not install thumbturn 09-509-027 on inside. Install chassis in the locked position. Replace cloverleaf cam L583-153 with straight cam B502-948 (Everest 29™), L583-255 with K510-680 (IC and SFIC) and install on outside.	Cams B502-948 (Everest 29), K510-680 (IC and SFIC) or L583-476 or L583-477 for modular cylinders	 B502-948    K510-680    L583-476    L583-477 <small>1 1/8" / 1 3/8" / 1 3/8"    1 1/4" / 1 1/2" / 1 3/4"</small>
Do not install thumbturn 09-509-027 on inside. Install cloverleaf cam cylinder on inside. Replace clover leaf cam L583-153 with straight cam B502-948 (Everest 29), L583-255 with K510-680 (IC and SFIC) and install on outside.	Mortise cylinder assembly and cams B502-948 (Everest 29), K510-680 (IC and SFIC) or L583-476 or L583-477 for modular cylinders	 B502-948    K510-680    L583-476    L583-477 <small>1 1/8" / 1 3/8" / 1 3/8"    1 1/4" / 1 1/2" / 1 3/4"</small>
Do not install thumbturn unit 09-509-027 on inside. Install chassis in the locked position. Install inside lever with L285-150 mounting plate; do not install outside lever or cylinder.	Mounting plate L283-150	 L283-150
Do not install thumbturn unit 09-509-027 on inside. Install cloverleaf cam cylinder on inside and outside.	Mortise cylinder assembly and cam L583-153	 Mortise Cylinder Assembly    L583-153    L583-274    L583-275 <small>1 1/8" / 1 3/8" / 1 3/8"    1 1/4" / 1 1/2" / 1 3/4"</small>
Do not install thumbturn unit 09-509-027 on inside. Install chassis in the locked position. Replace cloverleaf cam L583-153 with straight cam B502-948 (Everest 29), L583-255 with K510-680 (IC and SFIC) and install on outside. Install inside lever with L285-150 mounting plate; do not install outside lever.	Cams B502-948 (Everest 29), K510-680 (IC and SFIC), mounting plate L283-150 or L583-476 or L583-477 for modular cylinders	 L283-150    B502-948    K510-680    L583-476    L583-477 <small>1 1/8" / 1 3/8" / 1 3/8"    1 1/4" / 1 1/2" / 1 3/4"</small>
Do not install thumbturn unit 09-509-027 on inside. Install chassis in the locked position. Replace cloverleaf cam L583-153 with straight cam B502-948 (Everest 29), L 583-255 with K510-680 (IC and SFIC) and install on outside. Install inside lever on outside with L283-150 mounting plate; do not install inside lever.	Cams B502-948 (Everest 29), K510-680 (IC and SFIC), mounting plate L283-150 or L583-476 or L583-477 for modular cylinders	 L283-150    B502-948    K510-680    L583-476    L583-477 <small>1 1/8" / 1 3/8" / 1 3/8"    1 1/4" / 1 1/2" / 1 3/4"</small>
Install cloverleaf cam cylinder on outside; do not install thumbturn assembly 09-509-027 on inside. Install inside trim on outside with L283-150 mounting plate.	Mounting plate L283-150	 L283-150

# Electrified Lock Function

## Applications:

Security control centers, cashier rooms, fire safety exits, stairwell doors, telephone equipment rooms, computer rooms, hospital equipment and narcotics storage areas.

## Regulating Devices:

Recognition Systems, Inc., HandReaders, wall switches, security consoles, access card readers, thermo-sensitive devices, smoke and fire alarms, telephone access controls, automatic time devices and computerized controls.



**L9080PEL**  
**L9080PEU**  
**L9082PEL**  
**L9082PEU**

All installations should be in accordance with local electrical codes and National Electrical Code, NFPA 70.

## Electrical Requirements for EL or EU

Voltage: 24V AC or 24V DC (maximum 26V, minimum 22V)  
Peak Current: Amps 1.3 at 5- to 10-second intervals  
Holding Current: Amps .135 between peak current intervals  
Operating Temperature: Maximum +151° F, minimum -31° F


## Micro Switch Electrical Requirements for Request to Exit (RX) Function

Amps: 1.0  
Volts: 24 AC or DC  
Peak Load: Amps, 5; volts, 250 AC or DC

## Replacement Kit

L283-053 – Solenoid and driver, EL or EU

Typical Wiring Diagram for Electrified L-Series Locks



## Typical Installation

- Electrified L-Series locks contain a transistorized circuit that provides full voltage to the solenoid upon initial application of electrical power and at 5- to 10-second intervals.
- Each lock should preferably have its own 24-volt transformer. Two or more locks may be operated in parallel from a single transformer, provided it has the necessary current rating.

**NOTE:** DO NOT connect locks in series from a higher voltage rated transformer.


- We DO NOT recommend that these locks be connected to a supply circuit that also contains electromagnetic devices. If an electromagnetic device is connected to the supply circuit, the resulting transient voltages could damage the lock. The transient voltage must be carefully suppressed at the equipment producing them before connecting the lock to the same circuit.
- A varistor rated at 35 volts (peak recurrent) may be used for transient voltage protection.

## Cylinder Types



### Standard Cylinders

Schlage locks are provided with cylinders precision-built to extremely close tolerances and the highest standards of accuracy. Using only solid brass bar stock plugs and shells, phosphor bronze springs, and nickel silver keys and bottom pins ensures long life and ease of operation. Our 6-pin Everest 29™ cylinders in S123 keyway with two patented keys are standard for stock. S145 is standard for new master key systems.



### Primus XP Access Control and Primus® High Security Cylinders

Primus XP access control and high security cylinders are available to add patented key control and varying degrees of geographical exclusivity to most Schlage 6-pin key systems, whether Everest 29™ or Classic keyways.

In addition to a conventional pin tumbler mechanism, Primus cylinders incorporate a patented finger pin and sidebar design providing a “dual-locking” cylinder that is picking and bumping resistant. Resistance to drilling and other physical attack is optional by specifying 20-500 Series UL437 Listed cylinders.






### Primus XP Lockout Cylinders

For doors where it is frequently desirable to disable all keys from operating the lock temporarily use lockout cylinders. The special lockout key can be removed while the plug is turned to the 11 o'clock position, preventing all normal operating keys, including master keys, from fully entering the cylinder.



Suggested applications for lockout cylinders include laboratories, dark rooms, clean rooms and exterior doors to dormitories.

Schlage will not master key lockout cylinders.



# Standard (Non-IC) Cylinders

## Standard (Non-IC) Mortise Cylinders



Design	Function	Cylinder Mechanism				
		Conventional	Primus	Primus UL437	Primus Lockout	Primus UL437 Lockout
<b>L &amp; N Escutcheons</b> (cylinders and spring only)	All Except Below	30-021	20-793	20-593	20-717**	20-517**
	L9060P Outside	26-021	20-701	20-501	20-501	20-515**
	L9485, L9486 Faculty Restroom	30-022*	N/A	N/A	N/A	N/A
<b>L Escutcheon with concealed shell cylinder</b> (C suffix)	All Except Below	30-004	20-789	20-589	N/A	N/A
	L9080P Outside	26-023	N/A	N/A	N/A	N/A
	L9485, L9486 Faculty Restroom	30-005*	N/A	N/A	N/A	N/A
<b>Sectional Trim and L400-Series</b> (cylinder with compression ring & spring)	All Except Below	30-001	20-787	20-587	20-717	20-517
	L9060P Outside	20-001	20-700	20-500	20-715	20-515
	L9060P Outside	30-002*	N/A	N/A	N/A	N/A

\* Specify door hand for hotel function cylinders.

\*\* Discard compression ring for Lockout cylinders with escutcheon trim.


**Finishes:** 605, 606, 612, 613, 619, 625, 626, 629 and 630.

Concealed shell cylinders available in 606 and 626 only.

6-pin Everest 29 S123 keyway standard for stock cylinders; S145 standard for new key systems.

Standard cylinder lengths: sectionals (rose) trim = 1 1/8" (29 mm), escutcheon trim = 1 1/4" (32 mm).

Optional cylinder lengths are in 1/8" (4 mm) increments ranging from 1 1/8" to 1 3/4" (29 mm to 44 mm).



## Full-Size Interchangeable Core Cylinders

Schlage figure-8 interchangeable core (IC) cylinders allow immediate rekeying at the door. Simply use the special control key to replace the core in seconds. Full-size IC cylinders can be integrated into any existing 5- or 6-pin Schlage key system with no adverse effects on keying capacity. Convert existing mortise locks to interchangeable core merely by replacing the old cylinder with the IC cylinder and proper collar(s).

For ordering information see page 35.


### Full-Size IC Mortise Cylinders



Design	Function	Core Mechanism		
		Conventional	Primus	Primus UL437
<b>L &amp; N Escutcheons</b> (cylinders with compression ring)	All Except Below	30-008	20-798	30-007
	L9060P Outside	30-030	20-782	30-032 + 36-083
	L9485P, L9486P Faculty Restroom	30-010*	N/A	30-007
<b>Sectional Trim and L400-Series</b> (cylinder with compression ring, spring and 3/8" blocking ring)	All Except Below	30-138	20-776	30-137
	L9060P Outside	20-061	20-783	30-032 + 36-083 + 35-082-037
	L9485P, L9486P Faculty Restroom	30-140*	N/A	N/A


\* Faculty Restroom cores are handed. Specify hand of door. Finishes: 605, 606, 611, 612, 613, 619, 625, and 626. Standard cylinder length is 1 1/2".

### Full Size Interchangeable Cores Only



Number	Description
23-030	Conventional core
20-740	Primus core
30-120	Hotel function core (Specify hand of door)

Available 606 and 626 finish only.  
Standard keyway: 6-pin Everest 29™ S123 for stock, S145 for new master key systems



## Small Format Interchangeable Core (SFIC) Cylinders

The L-Series lockset can be ordered to accept small format interchangeable cores (SFIC) compatible with manufacturers such as Falcon, Arrow and Best; cams are easily changeable.

To order Schlage L-Series mortise locks with SFIC cylinders less core, change suffix P to BD. Example: L9453BD. To order locks with Everest 29™ R Family restricted keyway cores, change suffix to GD. To order with keyed construction cores, change suffix to HD. To order with disposable construction cores, change suffix to BDC.

For ordering information see page 35.


### Standard (Non-IC) Mortise Cylinders



Design	Function	Core Mechanism			
		Everest 29™ Restricted (GD Suffix)	Keyed Construction (HD Suffix)	Disposable Construction (BDC Suffix)	Housing Less Core (BD Suffix)
L & N Escutcheons (cylinders with compression ring and spring)	All* except L9060 Outside	80-308	80-138	80-115	80-108
	L9060 Outside	30-030	20-782	30-032 + 36-083	80-104
Sectional Trim and L400-Series (cylinder with compression ring, spring and 1/4" blocking ring)	All* except L9060 Outside	30-138	20-776	30-137	80-101
	L9060 Outside	80-304 + 36-082-025	80-134 36-082-025	80-112 36-082-025	80-104 36-082-025

Finishes: 605, 606, 612, 613, 619, 625, and 626.  
Standard cylinder length is 1 3/8".

### Small Format Interchangeable Core Only



Number	Description
80-036	7-Pin uncombined Everest 29 R Family restricted keyways
80-037	7-Pin combined Everest 29 R Family restricted keyways
80-043	6-Pin uncombined Falcon / Best keyways
80-033	7-Pin uncombined Falcon / Best keyways

Available 606 and 626 finish only. Specify keyway for existing systems.  
80-033 and 80-043 cores are available in A, D, E, F, G, H, J, K, L, and M keyways.  
Schlage assigns the keyway when establishing new Everest 29 restricted key systems.

# Blocking and Compression Rings

36-079




Blocking Ring. Specify finish and dimension. Not to be used with 36-083.

36-082



Blocking Ring. Specify finish and dimension. Use with 36-083.

36-083



Compression Ring and Spring. Specify finish and dimension.

L538-195



Compression Spring.

## Dimensions for Blocking Rings

Blocking Ring Length	Dimension
1/8"	012
3/16"	018
1/4"	025
5/16"	031
3/8"	037
7/16"	043
1/2"	050


## Full-Size Core Blocking Ring Requirements

Function	Trim	Door Thickness			
		1 3/8"	1 3/4"	2"	2 1/4"
		Dimension			
L9050, L9070, L9080, L9410 (disc), L9453, L9456, L9460 per XL11-886 or XL11-635, L9464 per XL11-886, L9465, L9473, L9480, L9496	Rose	050	037	025	025
	Escutcheon	025	012	N/R	N/R
L9485	Rose	—	037	025	025
	Escutcheon	—	012	N/R	N/R
L9486	Rose	012	N/R	N/R	N/R
	Escutcheon	025	012	N/R	N/R
L9060, L9071, L9077, L9082, L9457, L9462 per XL11-886, L9466, L9482	Rose	—	050	043	031
	Escutcheon	025	012	N/R	N/R
L460, L464, L496, L9460, L9464	Rose Trim	050	037	025	025
L462, L463, L9462, L9463	Rose Trim	—	050	043	031

## Full-Size Core Blocking Ring Requirements

Function	Trim	Door Thickness			
		1 3/8"	1 3/4"	2"	2 1/4"
		Dimension			
L9050, L9060, L9070, L9071, L9077, L9080, L9082, L9453, L9456, L9457, L9462 per XL11-886, L9465, L9466, L9473, L9482	Rose	037	025	012	N/R
	Escutcheon	N/R	N/R	N/R	N/R
L9050, L9060, L9070, L9080, L9082, L9410 (disc), L9453, L9456, L9460 per XL11-886 or XL11-635, L9464 per XL11-886, L9465, L9466, L9473, L9480, L9496	Rose	—	050	037	025
	Escutcheon	018	N/R	N/R	N/R
L460, L464, L496, L9460, L9464 L462, L463, L9462, L9463	Rose Trim	037	025	012	N/R
	Rose Trim	—	050	037	025

## Classroom Thumbturn Cylinders



These cylinders are for L463 and L9463 classroom function deadlocks. They are handed. They have a rotational stop in one direction to prevent locking from the inside, but allow unlocking. Cylinders are field-reversible by changing the position of the rotational stop. All cylinders furnished with L583-254 cam.

Number	Collar(s)
09-900	None
09-904	Compression ring and spring
09-905	For 1 <sup>3</sup> / <sub>4</sub> " doors: compression ring, spring and 1/8" blocking ring
09-907	For 1 <sup>3</sup> / <sub>4</sub> " doors: compression ring, spring and 1/8" blocking ring

Specify hand of door and finish. 1<sup>1</sup>/<sub>8</sub>" length standard. 09-900 and 09-905 also available in 1/8" increments up to 1<sup>3</sup>/<sub>4</sub>".

## Mortise Cylinder Cams

### Most Functions

L400 and L9000 Series



L583-153  
Everest 29 and  
Primus



L583-254  
Classic  
Conventional



L583-255  
All IC


L9060 Outside Only



B502-948  
Everest 29 and  
Primus



B502-191  
Classic  
Conventional



K510-680  
All IC

### Modular Cylinder Cams



L583-475  
Classic Conventional



L583-474  
Everest 29 & Primus XP


## Cams Screws



- B502-942 Everest 29 and Primus (non-IC)
- B502-468 Classic Conventional (non-IC)
- L583-333 All full-size interchangeable core
- B520-484 All small format interchangeable core

## IC Installation Tool


This tool is used to install and remove mortise cylinder housings and test mortise cylinder cam action for both small format and full-size interchangeable core cylinders. Its other ends are designed to install the driver and retainer for full-size IC in Schlage key-in-knob/lever locksets.



M504-413  
(Order as needed)

## Armored Fronts

L-Series armored fronts are produced from brass, bronze or stainless steel material, finished to match lock trim and furnished complete with screws. Numbers for ordering separately or with locks are listed below. Armored fronts are specified in latch column of order form.



Standard Square  
Corner


1 1/4" (32 mm) width

Square Corner		Description
1 1/4" (32mm) Width	1 1/16" (27mm) Width	
09-662	09-668	Latch: L9010, 9040, 9044
09-663	09-669	Deadlatch: L9050, 9056, 9060, 9070, 9071, 9080, 908
09-664	09-670	Latch x deadbolt: L9444, 9456, 9457, 9465, 9466, 9473, 9496
09-665	09-671	Deadbolt: L9460, 9462, 9463, 946
09-666	09-662	Deadlatch x deadbolt: L9453, 9480, 9485, 948
09-661	09-667	Blank (no holes): L9175, L917
09-713	----	Deadlatch, non-UL: L9076, 9077 (holdback functions)
09-717	----	Deadbolt: L400-Series


**Note:** For 1 3/8" (35mm) doors, 1 1/16" (27mm) front should be specified.

# Strikes

All L-Series strikes are produced from brass, bronze or stainless steel material, finished to match lock trim, and furnished complete with screws. Numbers for ordering separately or with locks are listed below.



**Standard for L9000**  
10-072  
1 1/4" x 4 7/8"  
x 1 3/16" Lip  
32 mm x 124 mm  
x 30 mm



**Armored Front Strike**  
10-091  
1 3/4" x 8" x 1 3/16" Lip  
32 mm x 203 mm  
x 30 mm



**Wood Frame Reinforcer**  
37-015



**Standard for L400**  
10-079  
1 1/8" x 3 1/2"  
32 mm x 89 mm



**Optional for L400**  
10-078  
1 1/4" x 4 7/8"  
32 mm x 124 mm

Number	Lip Length	Description
10-072	1 3/16" (30mm)	L9000 Standard
	7/8" (22mm), 1" (25mm), 1 1/2" (38mm)	L9000 Optional
	1 3/4" (44mm), 2" (51mm)	L9000 Special lip
10-073	No Lip	L9460-Series deadlocks
10-075	No Lip	1/2" (13mm) Rabbeted (use with 1 1/16" (27mm) armor)
10-078	No Lip	1 1/4" x 4 7/8" with box, L400 optional
10-079	No Lip	1 1/8" x 3 1/2" with box, L400 standard
10-091*	1 3/16" (30mm)	Armored front strike, no box
K510-053	---	Strike box for 10-079
K10-066	---	Strike box, all except 10-079


\*Specify hand of inactive leaf.

# Door Handing

One of the revolutionary features of the L-Series mortise lock is that handing can be done by the distributor or installer quickly and easily without opening the lock case. This feature allows a Schlage distributor to order L-Series locks as stock and customize the handing to each order's specification. This means off-the-shelf delivery to meet today's fast-track construction requirements. These mix-and-match lever-with-knob combinations, along with a quickly reversible lock chassis, provide the ultimate in stocking, ordering and installation flexibility. Orders can be filled from stock, minimizing delivery problems.

## Changing Lock Hand

No more than two simple steps are required to change the hand of any L-Series lock. Rotate the latch unit 180° and/or change the catch screw position.




### A. Changing Latchbolt Handing

Remove armored front. Pull latchbolt away from chassis and rotate complete unit 180° to reverse the door handing. Reinstall armored front.

### B. Change Chassis Handing

Remove catch screw from one side of chassis and install on opposite side. For RH and RR, the catch screw will be on the lock case side. For LH and LR, the catch screw will be on the lock case cover.

\*Catch screw location reversed for Vandlgard function. For first time users, an instructional video is available.



The hand is determined by the direction the door swings when viewed from the exterior or corridor side of the door.

# Specifications

## Handing:

L9000-Series lock bodies are field-reversible without disassembly.  
L400-Series locks are non-handed.

## Door Thickness:

1<sup>3</sup>/<sub>4</sub>" (44 mm) standard. 1<sup>3</sup>/<sub>8</sub>" (35 mm) to 2<sup>1</sup>/<sub>2</sub>" (64 mm) optional. Over 2<sup>1</sup>/<sub>2</sub>" (64 mm) door ranges vary by function. No escutcheon available for 1<sup>3</sup>/<sub>4</sub>" (44 mm) doors standard. 2" to 2<sup>3</sup>/<sub>8</sub>" (51 mm to 60 mm) optional. Specify door thickness if other than 1<sup>3</sup>/<sub>4</sub>".

## Backset:

2-3/4" (70 mm) only.

## Armored Front:

L9000-Series: 1<sup>1</sup>/<sub>4</sub>" x 8" x 7/32" (32 mm x 203 mm x 6 mm) standard.  
1<sup>1</sup>/<sub>16</sub>" x 8" x 1<sup>7</sup>/<sub>32</sub>" (27 mm x 203 mm x 6 mm) optional.  
L400-Series: 4<sup>7</sup>/<sub>16</sub>" x 3<sup>5</sup>/<sub>8</sub>" x 1" (113 mm x 92 mm x 25 mm)

## Case Size:

L9000-Series: 4<sup>7</sup>/<sub>16</sub>" x 6<sup>1</sup>/<sub>16</sub>" x 1" (113 mm x 154 mm x 25 mm)  
L400-Series: 4<sup>7</sup>/<sub>16</sub>" x 3<sup>5</sup>/<sub>8</sub>" x 1" (113 mm x 92 mm x 25 mm)

## Spacing:

Knob or lever to cylinder, 3<sup>7</sup>/<sub>8</sub>" (98mm); knob or lever to thumbturn hub, 2<sup>11</sup>/<sub>16</sub>" (68mm).

## Bolts:

1" (25mm) throw stainless steel deadbolt and 3/4" (19mm) throw stainless steel latch with anti-friction tongue.

## Exposed Trim:

**Knobs:** #41 and #42 heavy-duty wrought brass, bronze or stainless steel knobs match D-Series knobs.  
**Levers:** Forged brass or bronze and cast stainless steel. Designs available to match D-Series levers.

**Escutcheons:** L escutcheons are cold-forged brass or bronze and stainless steel. N escutcheons are heavy wrought reinforced brass, bronze and stainless steel.

**Trim Combinations:** Available with knob both sides, lever both sides, or knob and lever with rose or escutcheon both sides.

## Strike:

L9000-Series: ANSI curved lip strike 1<sup>1</sup>/<sub>4</sub>" x 4<sup>7</sup>/<sub>8</sub>" (32 mm x 124 mm) x 1<sup>3</sup>/<sub>16</sub>" (30 mm) lip to center with dust box standard. L400-Series: 1<sup>1</sup>/<sub>8</sub>" x 3<sup>5</sup>/<sub>8</sub>" (29 mm x 92 mm) with dust box.

## Cylinder & Keys:

6-pin Everest 29™ S123 keyway cylinder with two patented keys standard.

## Keying Options:

Interchangeable core and Primus Access Control and high security cylinders. Master keying, grand master keying and construction keying.

# Certifications

## ANSI:

L9000: ANSI A156.13 Series 1000, Grade 1 Operational and Security, UL Listed for 3-hour fire door (except L9076 and L9007). With interchangeable FSIC core cylinders: Grade 2 Security; with interchangeable core SFIC cylinders: Grade 3 Security.

**With Concealed Shell Cylinder:** A156.13 Grade 1 Operational and Security. ANSI/ASTM F476-76 Grade 40, UL Listed. L400: ANSI A156.5 Grade 1

## California State Reference Code:

**(Formerly Title 19, California State Fire Marshal Standard)** All levers with returns comply; levers return to within 1/2" of door face.

## UL / cUL:

All locks listed for A label single doors, 4' by 10'. Letter F and UL symbol on latch front indicate listing. Electrified functions are UL19X Listed for single-point locking applications. UL437 Listed locking cylinder optional: specify Primus 20-500 Series cylinder.





Ingersoll Rand (NYSE:IR) advances the quality of life by creating and sustaining safe, comfortable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Schlage®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; secure homes and commercial properties; and increase industrial productivity and efficiency. Schlage is the leader in security devices, trusted for 90 years, spanning both the commercial and residential markets. Ingersoll Rand is a \$14 billion global business committed to a world of sustainable progress and enduring results.



[securitytechnologies.ingersollrand.com](http://securitytechnologies.ingersollrand.com)

[ingersollrand.com](http://ingersollrand.com)