

OCALA Engineered



493 Bayfront



529 Oceanside



shawfloors.com







	US Units	Metric Units
Style Number	SW590	
Construction	Engineered	
Species	Maple	
Nominal Overall Thickness	3/8"	8.2 mm
Nominal Width	5"	127 mm
Finish	ScufResist Platinum	
Gloss Level	40%	
Surface Texture	Smooth	
Edge Description	Pillowed	
End Description	Pillowed	
Profile	Tongue And Groove	
Weight per Carton	33 lbs	14.96 kg
SQFT per Carton	23.66 sq ft	2.19 sq m
SQFT per Pallet	1419.6 sq ft	131.88 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	Moderate	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	Lifetime	
Commercial Warranty	5 Year Commercial	
All measurements are nominal.	Cartons may include random lengths.	

Features

The smooth surface of Ocala is sophisticated and refined - perfect for urban and contemporary settings. Also available in a scraped surface version, Clearwater.

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are nonstocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)

<u> </u>	\square
----------	-----------







SSO38





SFR38 Flush Reducer

SOR38 *Overlap Reducer

SFS38	
Flush Stairnose	*O\

SCR38 verlap Stairnose Threshold / Carpet Reducer

TMD78 T-Molding



Quarter Round



