



369 Saggio




937 Nero




1170 Avorio




1171 Sabbia



4005 Zaffiro



5212 Grigio



5213 Toratora



1171 Sabbia, 1170 Avorio

| | | |
|-----------------------|--|------------------------|
| Style Name | NOVARA | |
| Style Number | 5684V | |
| Construction | Heavy Commercial Luxury Vinyl Tile | |
| Class / ASTM F1700 | Class III Printed Film Vinyl Tile, Type B (embossed) | |
| Attached Underlayment | No | |
| Finish | ExoGuard® | |
| | U.S. | Metric |
| Nominal Dimensions | 24 in w, 24 in l | 61 cm w, 61 cm l |
| Actual Dimensions | 24 in w, 24 in l | 60.96 cm w, 60.96 cm l |
| Wear Layer Thickness | 20 mil (0.02 in) | 0.51 mm |
| Overall Thickness | 0.197 in | 5 mm |
| Installation | Direct Glue | |

Packaging

| | | |
|----------------|----------|-----------|
| Pieces per box | 8 pcs | |
| Area per box | 31 sq ft | 2.88 sq m |
| Weight per box | 56.5 lbs | 25.63 kg |

Performance Testing

| | |
|-------------------------------------|-----------------|
| Resistance to Heat (ASTM F1514) | Passes |
| Resistance to Light (ASTM F1515) | Passes |
| Resistance to Chemicals (ASTM F925) | Passes |
| Radiant Panel (ASTM E648) | Passes, Class I |
| Slip Resistance (ASTM D2047) | ADA compliant |

Warranties

Commercial Limited Underbed Bond Warranty S150/4151/LokWorx+ Resilient
 Resilient 15 Year Commercial Limited

Environmental

| | |
|--------------------|---------------------------------------|
| Indoor Air Quality | FloorScore® Certified |
| Recycled Content | Pre-consumer - 0%, Post-consumer - 0% |

Specifications are subject to nominal manufacturing variance.
 Material supply and/or manufacturing processes may necessitate changes without notice.

