



## VESSEL SINK

### INSTALLATION INSTRUCTIONS

Before installing, read entire Vessel Sink Installation Instructions. Observe all local building and safety codes.

We recommend consulting a professional if you are unfamiliar with this type of installation. Signature Hardware accepts no liability for any damages to the floor, walls, plumbing or for personal injury during installation.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-855-715-1800. If you need assistance or have questions while installing your sink, contact Customer Service.

### TOOLS AND MATERIALS:

Damp Cloth


Neutral Cure Silicone Sealant

Thread Sealant

Basin Wrench

### SINK INSTALLATION

1. Carefully place the sink upside down on the counter with a towel or other soft cloth beneath to prevent damage. Apply a continuous bead of silicone to the base of the sink where it will rest on the counter.
2. Turn the sink right-side-up and position it back over the 2" drain hole.
3. Remove any excess silicone with a damp cloth. Let the silicone dry for 24 hours. If a lavatory drain is included, move on to the **Drain Installation** section.



### DRAIN INSTALLATION

1. Disassemble the drain by removing the threaded tail piece, rubber sealing gaskets, friction washer and lock nut from the drain body.
2. Place thread sealant on the threaded section of the tail piece and reattach to the drain body. Slide the flat rubber sealing gasket up the tail piece to the top of the drain body. This gasket will create a water tight seal between the drain flange and sink.
3. Place the drain in the drain hole in the sink. On the underside of the counter, attach the tapered rubber gasket. With the flat side facing down, slide the gasket up the threaded shank until it makes contact with the bottom of the sink.
4. Slide the friction washer up to meet the rubber gasket. Thread the lock nut onto the threaded shank. Hand-tighten and make sure that the drain is properly aligned. When ready, finish tightening with a basin wrench to secure the drain.



## **SINK MATERIAL DESCRIPTION AND CARE**

Copper sinks are specially designed for both durability and beauty. Created with a single sheet of heavy gauge copper, our copper farmhouse sinks have no internal welds, strengthening the sink's structure and preventing leakage. The apron front is welded with solid copper by skilled artisans, ensuring both aesthetic appeal and quality.

Copper sinks will patina with time and normal use creating a much sought-after living finish. Because of copper's natural composition, cleaning is easy. Simply rinse after each use to rid the surface of any soap or dirt and wipe dry. Apply wax, such as Table Top Wax, at least once every 15-20 days to keep your copper sink in its original condition and prevent the natural aging process. For a more thorough cleaning, wash occasionally with dish soap and a sponge.

Do not use copper or silver cleaners, or any abrasive or harsh chemicals on your copper sink. Avoid contact with hot pots or pans, as this may cause distortion due to copper's low melting temperature.