

# CAST IRON DROP-IN SINK

## INSTALLATION INSTRUCTIONS

Before installing, read entire Drop-In Sink Installation Instructions. Observe all local building and safety codes.

For this installation it is assumed that the countertop has been cut to the dimensions of the sink. We recommend consulting a professional if you are unfamiliar with this type of installation, Signature Hardware accepts no liability for any damages to the floor, walls, plumbing or for personal injury during installation.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-855-715-1800. If you need assistance or have questions while installing your sink, contact Customer Service.

#### **TOOLS AND MATERIALS:**

Silicone Sealant Thread Sealant Damp Cloth Basin Wrench

Level

## INSTALLATION

1. Lower the sink into the sink cutout on the counter to confirm the sink will fit properly. The perimeter of the sink rim should connect with the counter while the sink bowl should sit completely inside the counter.

Tip: For easier installation, install the drain and faucet before attaching the sink to the counter.

- 2. Remove the sink and run a bead of silicone sealant around the sink cutout to seal the rim against moisture and leaks.
- 3. Carefully lower the sink back into the cutout and press the sink firmly into the sealant. Make sure that the sink is level and properly aligned.
- 4. With the sink in place, tighten the mounting clips (if included) on the underside of the sink.
- 5. Wipe away any excess sealant around the rim of the sink with a damp cloth

#### **DRAIN INSTALLATION**

- 1. Apply a bead of silicone sealant to the base of the strainer flange.
- 2. Place the flange in the drain opening in the kitchen sink.
- 3. If your drain has a disposer flange, use the directions supplied with the garbage disposer to attach the disposer and complete your installation. For drains with strainer baskets, slide the rubber gasket and friction washer up the strainer flange to the bottom of the sink.
- 4. Thread the lock nut onto the drain assembly. Hand-tighten and make sure that the drain is properly aligned. When ready, finish tightening with a basin wrench to secure the drain.



SIGNATURE HARDWARE

customer service: 1.855.715.1800 signature**hardware**.com



5. Secure the P-trap to the strainer flange with the provided compression nut and ferrule.

## MATERIAL DESCRIPTION AND CARE

Cast iron sinks are extremely durable and beautifully finished with a think enamel top layer. The enamel coating creates a beautiful glossy sheen and is nonporous, which prevents rust, tarnish, and allows for thorough cleaning. The enamel finish prevents corrosion and acid, which helps to keep your sink looking new and performing well over time.

Cleaning and maintenance are easy. A thorough rinsing and wipe-down with a soft cloth is recommended after each use.

