


© Copyright 1997 SLOAN VALVE COMPANY Printed in U.S.A.

Hydraulic Royal[®] Model Flushometer



Description

Concealed Hydraulically Operated Urinal Flushometer, for 3/4" top spud urinals.

Flush Cycle

- ☐ Model 997 Water Saver (1.5 gpf/5.7 Lpf)
 - ☐ Model 997-1 Low Consumption (1.0 gpf/3.8 Lpf)
 - ☐ Model 997-0.5 (0.5 gpf/1.9 Lpf)

Specifications

Quiet, Concealed, Diaphragm Type, Rough Brass Urinal Flushometer for either left or right hand supply with the following features:

- Dual Filtered By-pass
- ADA Compliant Non-Hold-Open feature type Actuator (specify Actuator type listed below)
- ¾" I.P.S. Wheel Handle Bak-Chek™ Angle Stop
- Adjustable Tailpiece
- Vacuum Breaker
- Elbow Flush Connection and Spud Coupling for 3/4" Exposed Top Spud
- Sweat Solder Adapter
- Diaphragm, Stop Seat and Vacuum Breaker to be molded from PERMEX™ rubber compound for Chloramine resistance
- Exposed parts Chrome Plated

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.6, and Military Specification V-29193.

L Dimension

Specify the "L" Dimension for the proper length of the Flush Connection. The "L" Dimension is equal to the Wall Thickness (to the nearest whole inch) plus 2^34 ".

Actuator Types: (please check one)

☐ FW	Fixture Wall Actuator (HY-33-A) (rear access required)
☐ MP	Metal Partition Actuator (HY-49-A)
□sw	Side Wall Mounted Actuator (HY-72-A)
MRFW	Metal Button Fixture Wall Actuator (HY-100-A) (rear access required)

MBPM Metal Button Panel Mount (HY-108-A)

See Actuator Specification pages in this section for details on Actuators. See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

Hydraulic Flushometer can also be provided in Regal® Models. All rough-in dimensions remain the same. Consult the factory.







Listed by I.A.P.M.O.

This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.

Made in the U.S.A.



SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL 60131 PHONE: 1-800 982-5839 • FAX: 1-800 447-8329 • http://www.sloanvalve.com