T-5001

SPEAKMAN[®]

Glennwynn™ 1-piece Elongated High-Efficiency Toilet

FEATURES:

- Construction: one piece construction
- Material: high quality vitreous china
- WaterSense: high efficiency, low consumption
- Bowl: rimless
- Flush: tornado flushing action
- Glaze: ultra glazed surface
- Rough-in: 12"
- 2" Fully glazed trapway
- Height: perfect height
- 100% Factory tested.
- Included materials: 3" adjustable flush valve, 3" adjustable flapper, slow-close toilet seat, chrome trip lever, closet bolts
- 100% Factory tested - 1000 Map score at 1.28gpf

AVAILABLE COLORS:

• White

NOMINAL DIMENSIONS:


• 28-3/8" x 16-3/8" x 28-3/4" (720mm x 415mm x 730mm)

STANDARDS:

- ASME A112.18.1/CSA B125.1 certified
- cUPC certified
- WaterSense certified
- ADA compliant







WARRANTY:

Visit www.speakman.com for full product warranty information

Product	Warranty Period Residential Installation	Warranty Period Commercial Installation
Vitreous China Material	Limited Lifetime	10 Year Limited
Mechanical Components	Limited*	Limited*
Seat	1 Year Limited	1 Year Limited

All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.
This toilet is designed to rough-in at a minimum dimension of 12" (305mm) from finished wall to c/l of outlet.
Supply not included with fixture and must be ordered separately.
This toilet is designed to rough-in at a minimum dimension of 12" (305mm) from finished wall to c/l of outlet.
Supply not included with fixture and must be ordered separately.
This toilet is designed to rough-in at a minimum dimension of 12" (305mm) from finished wall to c/l of outlet.
Supply not included with fixture and must be ordered separately.
This toilet is designed to rough-in at a minimum dimension of 12".
This toilet is designed to rough-in at a minimum dimension of 12".
This toilet is designed to rough-in at a minimum dimension of 12".
This toilet is designed to rough-in at a minimum dimension of 12".
This toilet is designed to rough-in at a minimum dimension of 12".
This toilet is designed to rough-in at a minimum dimension of 12".
This toilet is designed to rough-in at a minimum dimension of 12".
This toilet is designed to rough-in at a minimum dimension of 12".
This toilet is designed to rough-in at a minimum dimension of 12".
This toilet is designed to rough-in at a minimum dimension of 12".

Architect/Engineer Approval Space:

P: 800-537-2107 F: 800-977-2747 W: WWW.SPEAKMAN.COM

R: 02-NOVEMBER 2020