

ANYSTREAM 2000®

S-2005-HOTEL



S-2005-HB



S-2005-HS



GENERAL SPECIFICATION

Water conserving pressure compensating Autoflo® device reduces flow to 2.5 GPM/9.46LPM maximum, to meet existing ASME A112.18.1 standard. Brass threaded inlet with 1/2" NPSM inlet. There is also a dual action combination spray.

S-2005-HOTEL

Polished chrome plated Anystream S-2000® Showerhead. Spray adjusting T-handle. 2-1/2" face. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

S-2005-HB

Polished chrome plated Anystream S-2000® Showerhead. Spray adjusting T-handle. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

S-2005-HS

Polished chrome plated Anystream S-2000® Showerhead. Spray adjusting T-handle. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> BB	Bright brass (S-2005-HB only)
<input type="checkbox"/> BBHOTEL	Bright brass (S-2005-HOTEL only)
<input type="checkbox"/> BN	Brushed nickel finish (S-2005-HOTEL only)
<input type="checkbox"/> BP	Blister pack packaging (S-2005-HOTEL)
<input type="checkbox"/> SC	Satin chrome finish (S-2005-HB only)
<input type="checkbox"/> SN	Satin nickel finish (S-2005-HB only)
<input type="checkbox"/> WHT	White finish (S-2005-HB, S-2005-HS only)

This space for Architect/Engineer approval. _____

