SPEAKMAN® SE-690-CV

COMBINATION SHOWER & COVERED EYE/FACE WASH

DESCRIPTION

The SE-690-CV Safe-T-Zone[®] features the SE-490-CV covered eve/face wash with dual spray outlets, flip-top dust covers and stainless steel bowl combined on a powder coated galvanized steel stanchion with an impeller action deluge showerhead which is activated by a high visibility yellow pull rod.

SPECIFICATIONS

24" Showerhead: 8" Cycolac[®] yellow plastic (610mm) t Flow Control: Internal 20 gpm regulator 9¾" Valve: 1" NPT female brass, chrome-plated. Full flow (248mm) stay open ball valve 7'0" Activator: Powder coated yellow, aluminum triangular TO FLOOR 1 1/4" NPTE (2134mm) INLET pull rod 69" MAX Stanchion: 1¹/₄" IPS galvanized steel piping, brass fittings TO FLOOR Inlet & Waste: 1¹/₄" NPT female (1753mm) NOTE: PULL ROD SHOWN ROTATED 90° TO FLOOR Finish: DuraJadeTM powder coated finish 4h Performance: 20 gpm @ 20 psi EYE/FACE WASH: SE-490-CV **Bowl:** 300 series stainless steel Cover: 300 series stainless steel Spray Heads: (2) yellow ABS plastic spray outlets with flip-41 (1041mm) top dust caps Valve: 1/2" NPT female brass, chrome-plated full flow stay 6" (152mm) open ball valve Activator: Stainless steel push handle Performance: 3.8 gpm @ 30 psi Compliance: ANSI Z358.1 Universal Emergency Sign Included **OPTIONS** BH Brass showerhead **FLW** Flow switch **F**PV Freeze protection valve Job Name_____ HFO Hand/Foot operation Location **H** HS Hand-held spray **S**CV Self-closing shower valve Architect/Engineer _____ SPR Stainless steel pull rod Sales Representative **SPV** Scald protection valve □ SSBV Stainless steel ball valve Wholesaler **SSH** Stainless steel showerhead Date_____ Model # **T**TS Top supply \Box XPR Extended aluminum pull rod

5' 5"

(1651mm)

1 1/4" NPTF

WASTE