

A KOHLER COMPANY


ENSEMBLETM

71100112

36" (91.4 cm) AFD BATH/SHOWER

Features

- Compression molded from Sterling's exclusive solid Vikrell_® material
- Gentle sloping back, neck, and armrest in bath design
- Above floor drain rough-in
- Factory installed Vikrell® apron extension and plastic undersupport for ease of installation
- Modular 4-piece design
- Lightly pebbled bottom surface for sure footing
- Tongue-and-groove "snap together" design
- Durable high gloss finish
- 10 year consumer/3 year commercial limited warranty
- 18-1/4" (46.4 cm) bath depth (floor to top of dam)
- 60" (152.4 cm) x 37-1/2" (95.3 cm) x 75-1/2" (191.8 cm) complete unit rough-in dimensions include
- 60" (152.4 cm) x 36" (91.4 cm) x 74-1/4" (188.6 cm) complete unit finished dimensions





SYSTEM

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ANSI Z124.1.2
- ASTM E162
- ASTM E662
- IAPMO/UPC
- CSA International
- CSA B45

Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Complete Unit Description	Colors/Fin	Colors/Finishes	
71100112	36" (91.4 cm) AFD bath and wall surround, left drain	□ 0	☐ Other	
71100122	36" (91.4 cm) AFD bath and wall surround, right drain	0 0	☐ Other	
Model	Wall Component Description	Colors/Fin	Colors/Finishes	
71102100	Back wall	□ 0	☐ Other	
71103110	Left end wall	□ 0	☐ Other	
71103120	Right end wall	□ 0	☐ Other	
71104100	Complete wall set	□ 0	☐ Other	
71105100	End wall set		□ Other	

SterlingPlumbing.com

Visit us online for fixture color choices, detailed product information, color photos, installation instructions, care guides, and warranties. Sterling offers additional lines of plumbing products to complement the Sterling product you've chosen. Sign up for the Sterling monthly e-newsletter which showcases our latest product innovations. You may also call our Sterling Plumbing Answer Center from within the USA at 1-888-STERLING in addition to consulting with your local dealer. Sterling. Strong. Professional. Design.

ENSEMBLETM

Technical Information

Fixture*:	basin area	top area			
Bathing well	40" (101.6 cm) x 21" (53.3 cm)	52" (132.1 cm) x 29" (73.7 cm)			
To overflow	water depth	capacity			
	11" (27.9 cm)	40 gal (151.4 L)			

* Approximate measurements for comparison only.

Mod	el	door maximum width	door maximum height
	0112 0122	58-1/2" (148.6 cm)	56-1/2" (143.5 cm)

Installation Notes

Install this product according to the installation guide.

Size the drain hole clearance to fit the drain assembly that will be used.

Stud positioning is critical.

Studs should be positioned roughly as shown for support clip or roofing nail installation.

