

Manually Venting Double Hip, Pyramid

Double Hip, Pyramic and Flat Skylights




Frame Model 840B

KEY FEATURES

Truth Operator for Ease of Opening Integrated Bug Screen Bronze or Mill Finish

PRODUCT PROFILE



SPECIFICATIONS

Skylights shall be Sunoptics model 840B (curb mounted) as manufactured by Sunoptics Skylights, 6201 27th Street, Sacramento Ca. 95822 916/395-4700

Skylights shall be glazed ready for installation.

Skylight frames shall be fabricated from 6063 T5 aluminum, finish as specified. Frames shall have integral condensation and weepage gutters which drain interior moisture to the outside. Corners shall be mitered and welded. Skylight frames shall be thermally broken. The acrylic glazing shall be separated from the skylight frame with an EPDM rubber air seal gasket.

Skylights shall be operated using Truth Inc. chain drive manual operator and include a bug screen.

Skylights shall be glazed using CC2 acrylic, and/or polycarbonate in a pyramid or double hip configuration.

Note: Multi-glazed units default to include Insulated Thermal Break (ITBR), CTape, Weather Sweep (WSW) and screws. Single-glazed units default to not included any of these options.

Туре	SHGC	U-Value	VLT
Single Glazed Acrylic	.51	n/a	.74
Single Glazed Poly	.51	n/a	.70
Double Glazed	.42	.74	.68
Acrylic/Acrylic			
Double Glazed	.42	.74	.63
Poly/Acrylic			
Triple Glazed	.33	.62	.63
Acrylic/Acrylic/Acrylic			
Triple Glazed	.33	.62	.60
Poly/Acrylic/Acrylic			

Standard pole is 3 ft. and adjustable up to 5 ft. Also available with 3 ft. extensions.

ORDERING LOGIC

					>>>
DHP Double Hip Lens 204 208 201 202 282 303 305 306 308 301 404 405 406 407 408 401 555 506 507 508	14 18-5/8"x 18-5/8"4 140 27-1/4"x51-1/4" 180 27-1/4"x99-1/4" 190 26-5/8" x 26-5/8"4 181 34-5/8" x 34-5/8"4 182 34-5/8" x 34-5/8"4 183 38-5/8" x 38-5/8"4 184 39-1/4"x75-1/4" 185 39-1/4"x75-1/4" 180 39-1/4"x75-1/4" 180 39-1/4"x75-1/4" 180 39-1/4"x75-1/4" 180 51-1/4"x87-1/4"	Glazing SGZ Single Glaze DGZ Double Glaze TGZ Triple Glaze	Lens Material CC1 Polycarbonate 50CC2 50% IM Acylic	LENS COLOTS LENSWH LENSCL LENSWHCL LENSCLCL LENSWHWHWH LENSCLCL LENSCLCLCL LENSCLWHCL LENSCLWHCL LENSWHCLWH LENSCLWHCL LENSWHCLWH LENSCLWHCL	White (Single Glaze Default) ¹ Clear ¹ White Clear ² Clear White (Double Glaze Default) ² White White ² Clear Clear ² White White White ³ Clear Clear Clear ³ Clear White Clear (Triple Glaze Default) ³ White Clear White ³ Clear White White ³ White Clear Clear ³ White Clear Clear ³

<u>Unit Type</u>		
840B	Manually Venting Frame	

Skylight Frame Finish			
MI	Mill (Default)		
14/11	MIL:		

MI Mill (Defau
WH White
BZ Bronze
CF Custom

Options

(blank) No Options
ITBR Insulated Thermal Break
NITBR No Insulated Thermal Break
WSW Weather Sweep
NWSW No Weather Sweep
CTAPE Curb Seal Tape

NOCTAPE No Curb Seal Tape

1) Single Glaze 2) Double Glaze 3) Triple Glaze 4) Pyramid Lens only





