
FreeJack Surface Canopy





DESCRIPTION

Mounts to a standard 4" junction box with round plaster ring (provided by electrician). Vaulted version available for ceilings up to 40°. Electronic transformer inside 2" high, 4.5" diameter housing. One FreeJack port; for ceiling or wall.

INSTALLATION

This product can mount to either a 4" square electrical box with round plaster ring or an octagonal electrical box (not included). Transformer (included) fits in canopy. For ceiling or wall. If wall mounting, head should be no longer than 6".

DIMMING

120V IN/12V OUT and 120V IN/24V OUT dimmable with a standard incandescent dimmer (not included). 120V LED dimmable with a low-voltage electronic dimmer (not included). 277V LED dimmable with a 277V low-voltage electronic dimmer (not included). 277V IN/12V OUT dimmable with a 277V incandescent dimmer (not included).

OTHER INFORMATION

For use with any 12 or 24 volt halogen or 12 volt LED FreeJack pendant or head (sold separately)

WEIGHT

1lb / 0.45kg

ORDERING INFORMATION

700FJSF SHAPE OR SIZE		FINISH		VOLTAGE	
4 4V	4" ROUND SURFACE INTEGRAL TRANSFORMER 4" ROUND SURFACE VAULTED INTEGRAL TRANSFORMER	B C S	ANTIQUE BRONZE BLACK CHROME SATIN NICKEL WHITE	024	120V IN/12V OUT 120V IN/24V OUT
		**	VVIII1 L	277	277V IN/12V



7400 Linder Avenue Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

www.techlighting.com

700FJSF_	
FIXTURE TYPE:	
JOB NAME:	
NOTES:	

