

INSTALLATION INSTRUCTIONS

For Model 8725-A615B

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

PREPARING FOR INSTALLATION (Fig.1)

1. Shut off power at the fuse box or circuit breaker box. Remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Loosen Nuts (C) to remove Bottom Plate (F).
4. Secure bottom plate (F) to the structure. If necessary, plugs (E) may be used first.
5. Pull the black, white and ground wires out of the center hole of bottom plate (F).

CONNECTING THE WIRES (Fig. 2)

6. Next, connect electrical wires while supporting the lantern. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. If not, consult your electrician for proper grounding. After the wires are connected, tuck them carefully inside the wiring box through the center hole in the bottom plate (F) and the fixture body (D)

COMPLETING THE INSTALLATION (Fig. 1)

7. Align the fixture body (D) to bottom plate (F) and secure with nuts (C).
8. Loosen cap nuts (B) to remove Roof (A). Insert the glass panels (G) into fixture body (D) and secure them using the clips that are located on the bottom of the fixture body.
9. Install 3*60W B10.5 bulbs (not included) into the socket in accordance with the fixture's specification. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!!)**
10. After the installation, replace roof (A) and secure with cap nuts (B).

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

