Aquia® Wall-Hung Dual-Flush Toilet, 1.6GPF & 0.9GPF

FEATURES

- Dual-Max® flushing system, low consumption (1.6GPF/6.0LPF & 0.9GPF/3.4LPF)
- Optional CeFiONtect[™] ceramic glaze prevents debris, mold from sticking to ceramic surfaces, leading to fewer chemicals and less water in cleaning.
- Universal Height
- Wall-hung toilet can be paired with TOTO in-wall tank system as well as others

MODELS

- CT418FG#01 with CeFiONtect
- CT418F#01 without CeFiONtect
- SS204 SoftClose® seat (sold separately)
- SS114 SoftClose® seat (sold separately)
- SC134 commercial seat (sold separately)
- SC534 commercial seat (sold separately)
- WT151M In-wall tank system (pex pipe) (sold separately)
- WT152M In-wall tank system (copper pipe) (sold separately)

COLORS/FINISHES

Standard #01 Cotton

PRODUCT SPECIFICATION

This universal height, low consumption Dual-Max flushing system toilet shall be 1.6GPF & 0.9GPF. Toilet shall have optional CeFiONtect ceramic glaze. Toilet shall be mounted to in-wall tank system, elongated front bowl and wall-mounted push-button type trip lever. Toilet shall be TOTO Model CT418F(G)#01.







CODES/STANDARDS

- Meets or exceeds ASME A112.19.2/CSA B45.1, ASME A112.19.14
- Certifications: IAPMO (cUPC), EPA Watersense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance





Aquia® Wall-Hung Dual-Flush Toilet, 1.6GPF & 0.9 GPF

SPECIFICATIONS

Water Use
 1.6 GPF & 0.9GPF
 (6.0 LPF & 3.4LPF)

Flush System
Min. Water Pressure
Water Surface
Trap Diameter
Installation Height
Trap Seal
Dual-flush
8 psi (static)
5.5" X 4.75"
2-1/8"

• Warranty One Year Limited Warranty

Material Vitreous chinaShipping Weight CT418F(G) - 66.5lbs

Shipping Dimensions CT418F(G)

23-3/4" L X 15-3/4"W

X 17.5" H

INSTALLATION NOTES





