

COMPARISON CHART

NAME		NEOREST 600	NEOREST 550	NEOREST 500	NEOREST 550H
PRODUCT NUMBER		MS990CGR	MS980CMG	MS950CG	MS982CUMG
COLOR			Cotton (#01), Sedona Beige (#12)		
CLEANSE	REAR CLEANSE	•	•	•	•
	FRONT CLEANSE	•	•	•	•
	SOFT REAR CLEANSE	•	•	•	•
	OSCILLATING CLEANSE	•	•	•	•
	PULSATING CLEANSE	•	•	•	•
	INSTANTANEOUS WATER HEATING	•	•	•	•
	WATER PRESSURE CONTROL	7 Settings	7 Settings	7 Settings	5 Settings
WATER TEMPERATURE CONTROL	5 Settings	5 Settings	5 Settings	5 Settings	
NOZZLE POSITION ADJUSTMENT	•	•	•	•	
AIR	AIR PURIFIER (DEODORIZER)	•	•	•	•
	AIR DRYER	•	•	•	•
	AIR TEMPERATURE CONTROL	5 Settings	5 Settings	5 Settings	5 Settings
SEAT	HEATED SEAT	•	•	•	•
	HEATED SEAT TEMPERATURE CONTROL	5 Settings	5 Settings	5 Settings	5 Settings
	SOFT CLOSE SEAT AND LID	•	•	•	•
SENSOR	SEAT SENSOR	•	•	•	•
	AUTOMATIC OPEN AND CLOSE LID	•	•	•	•
	AUTOMATIC FLUSH	•	•	•	•
	REMOTE CONTROL	•	•	•	•
REMOTE CONTROL	REMOTE CONTROLLED SEAT AND LID	•	•	•	•
	REMOTE CONTROLLED FLUSH	•	•	•	•
	NIGHT LIGHT	•	•	•	•
	ANTIBACTERIAL COATING	•	•	•	•
HYGIENE	eWATER+	•	•	•	•
	REMOVABLE SEAT AND LID	•	•	•	•
	NOZZLE CLEANING BUTTON	•	•	•	•
	SELF-CLEANING NOZZLE	•	•	•	•
ENERGY SAVING	ENERGY-SAVE TIMER	3, 6, 9 Hours	3, 6, 9 Hours	3, 6, 9 Hours	3, 6, 9 Hours
	AUTO ENERGY SAVER	•	•	•	•
	ON / OFF BUTTON	•	•	•	•

POWER RATING		120V AC, 60Hz	120V AC, 60Hz	120V AC, 60Hz	120V AC, 60Hz
LENGTH OF POWER CORD		Maximum length 3 ft.	Maximum length 3 ft.	Maximum length 3 ft.	Maximum length 4 ft.
TOILET	FLUSH VOLUME	1.6 Gallon (6L) with 1.2 Gallon (4.5L) Light Flush	1.6 Gallon (6L) with 1.06 Gallon (4L) Light Flush	1.6 Gallon (6L) with 1.2 Gallon (4.5L) Light Flush	1.0 Gallon (4L) with .8 Gallon (3L) Light Flush
	FLUSH TYPE	Cyclone Siphon Jet	Cyclone Siphon Jet	Cyclone Siphon Jet	Cyclone Siphon Jet
WASHLET®	NOZZLE FLOW RATE	REAR	9 ~ 14.5 oz. / min.	9 ~ 14.5 oz. / min.	9 ~ 14.5 oz. / min.
		SOFT	9 ~ 14.5 oz. / min.	9 ~ 14.5 oz. / min.	9 ~ 14.5 oz. / min.
		FRONT	9.5 ~ 14.5 oz. / min.	9.5 ~ 14.5 oz. / min.	9.5 ~ 14.5 oz. / min.
DRYER	WATER TEMPERATURE	86°F ~ 104°F	86°F ~ 104°F	86°F ~ 104°F	86°F ~ 104°F
	AIR TEMPERATURE	104°F ~ 138°F	104°F ~ 138°F	104°F ~ 138°F	104°F ~ 138°F
	CAPACITY OF AIR	10.5 ft³ / min.	10.6 ft³ / min.	8.4 ft³ / min.	10.6 ft³ / min.
HEATED SEAT	SURFACE TEMPERATURE	Minimum: 79° F Maximum: 97° F	Minimum: 82° F Maximum: 97° F	Minimum: 79° F Maximum: 97° F	Minimum: 82° F Maximum: 97° F
	HEATER POWER CONSUMPTION	50W	50W	50W	50W
AIR PURIFIER	METHOD	Catalytic purification	Catalytic purification	Catalytic purification	Catalytic purification
	AIR VOLUME	5.5 ft³ / min.	5.5 ft³ / min.	5.5 ft³ / min.	5.5 ft³ / min.
WATER SUPPLY PRESSURE		Minimum: 20 psi Maximum: 80 psi	Minimum: 20 psi Maximum: 108 psi	Minimum: 20 psi Maximum: 80 psi	Minimum: 7 psi Maximum: 110 psi
WATER SUPPLY TEMPERATURE		33°F/1°C to 104°F/63°C	33°F/1°C to 104°F/63°C	33°F/1°C to 104°F/63°C	33°F/1°C to 104°F/63°C
AMBIENT TEMPERATURE		33°F/1°C to 104°F/63°C	33°F/1°C to 104°F/63°C	33°F/1°C to 104°F/63°C	33°F/1°C to 104°F/63°C
SIZE		W 17" x D 32.2" x H 22.2"	W 15.3" x D 25.2" x H 21.3"	W 17" x D 26.3" x H 20"	W 15.3" x D 27.7" x H 21.5"
TOTAL PRODUCT WEIGHT		Net: 108 lbs.	Net: 82.7 lbs.	Net: 81.5 lbs.	Net: 95.5 lbs.



Neorest 600



Neorest 550 - 550H



Neorest 500